

Industrial and Commercial

# G84-4100 Series Ultraslim Keyboards



# **Main Applications**

- Rack Mount Systems
- Airlines
- Bankina
- Education/Schools
- Manufacturing
- Medical Equipment
- Automotive Equipment
- Office/Data Entry
- White Box PCs
- Field Services
- Test Equipment
- Kiosk Applications
- POS/POT
- Transport

## **Key Features**

- Mechanical Keyswitches are Rated at 50 Million Actuations to Withstand Harsh Environments and Ensure Long Product Lifetime
- Size-reduced QWERTY Key Layout in Ultraslim 11" Form Factor Combines Maximal Space Efficiency with Comfortable Alphanumeric Data Entry
- "FN-Key" for Easy Access of Integrated Numeric Area Ensures Complete Function Support as with Full Size Keyboards
- All Product Available with PS/2 and USB Interface.
- Dual PS2/USB Interface allows for Easy Field Upgrade
- Optional 'Non-Windows' Key Layout

# **Main Part Numbers**

# G84-4100PPAUS

Beige 11" ultraslim PS/2 keyboard. US space reduced 83 position key layout without 'Windows keys'. Mechanical keyswitches with tampoprinted keycaps.

## G84-4100PRAUS

Black 11" ultraslim PS/2 keyboard. US space reduced 83 position key layout without 'Windows keys'. Mechanical keyswitches with tampoprinted keycaps.

## G84-4100LCMUS-0

Light grey 11" ultraslim keyboard. US space reduced 86 position key layout. Includes USB and PS/2 connectors. Mechanical keyswitches with tampoprinted keycaps.

## G84-4100LCMUS-2

Black 11" ultraslim keyboard. US space reduced 86 position key layout. Includes USB and PS/2 connectors. Mechanical keyswitches with tampoprinted keycaps.

## G84-4100LCAUS-0

Light grey 11" ultraslim keyboard. US space reduced 83 position key layout Includes USB and PS/2 connectors. Mechanical keyswitches with lasered keycaps.

## G84-4100LPAUS-0

Light grey 11" ultraslim PS/2 keyboard. US space reduced 83 position key layout Includes Mechanical keyswitches with lasered keycaps.

Additional product versions on request.



Industrial and Commercial

# G84-4100 Series Ultraslim Keyboards

#### **Part Number**





#### **Technical Data**

#### Interface

PS/2, USB

#### Current Input

max. 100 mA

## Cable Length

Approx. 1.75 m (non-coiled)

## **Key Layout**

Sized reduced 83/86 US key layout

**Weight** (without/with packaging) 0.4/0.5 kg

## Dimension

282 x 132 x 27 mm (keyboard) 285 x 135 x 30 mm (packaging)

# **Packaging Units**

42 per master carton 8 master cartons per pallet

#### **Keyswitch Lifetime**

50 million operations

# Storage Temperature

-20°C to  $60^{\circ}\text{C}$ 

## Operating Temperature

0°C to 50°C

## **Approvals**

cURus, FCC, CE, VDE, BSMI, C-Tick ('PT' and 'PC' Versions)

## **Delivery Volume**

Keyboard, Quick Guide,

# Warranty

2 years

For information on repairs or warranty status contact: Cherry Technical Support Phone: 800.510.1689

E-Mail: keyboardsupport@cherrycorp.com

#### Contact

Call, fax or visit our website for more information.

## **Cherry Electrical Products**

11200 88th Avenue Pleasant Prairie, WI 53158

Phone: Web:

262.942.6500 www.cherrycorp.com

E-Mail: Fax: sales@cherrycorp.com 262.942.6566 The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.

Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.