

PACT MCR-V2-10020-129-2000-1A1 - Current transformer



2905889

<https://www.phoenixcontact.com/us/products/2905889>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Window-type current transformer, 2000 A AC primary current; 1 A AC secondary current; accuracy class 1; 15 VA rated power

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 2905889 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | C444 |
| Product key | CK4A11 |
| GTIN | 4055626005003 |
| Weight per piece (including packing) | 701.3 g |
| Weight per piece (excluding packing) | 701.3 g |
| Customs tariff number | 85043129 |
| Country of origin | DE |

PACT MCR-V2-10020-129-2000-1A1 - Current transformer



2905889

<https://www.phoenixcontact.com/us/products/2905889>

Technical data

Product properties

| | |
|--------------|---------------------|
| Product type | Current transformer |
|--------------|---------------------|

Electrical properties

| | |
|--------------------------|--------------------------------|
| Rated insulation voltage | 1 kV (Phase/neutral conductor) |
|--------------------------|--------------------------------|

General

| | |
|-------------------|---------------------------------|
| Can be calibrated | no |
| Converter type | Window-type current transformer |

Input data

Current transformers

| | |
|----------------------------------|--|
| Rated power | 15 VA |
| Thermal rated short-time current | $I_{th} = 60 * I_n$ |
| Thermal rated continuous current | $I_d = 1.2 * I_n$ |
| Rated surge current | $I_{dyn} = 2.5 * I_{th}$ |
| Rated frequency f_n | 50 Hz 60 Hz |
| Primary rated current I_{pn} | 0 A AC ... 2000 A AC |
| Primary rated current range | 1 A AC ... 4000 A AC (depends on type) |
| Can be calibrated | no |
| Converter type | Window-type current transformer |

Output data

Signal

| | |
|----------------------------------|----------------|
| Designation | Current output |
| Secondary rated current I_{sn} | 1 A AC |
| Surge current limitation factor | FS 5 |
| Accuracy class | 1 |

Connection data

| | |
|----------------------------------|--|
| Connection method | Screw connection |
| Conductor cross section flexible | 2x 2.5 mm ² ... 4 mm ² (Secondary terminals) |

Dimensions

Item dimensions

| | |
|--------|--------|
| Width | 30 mm |
| Height | 156 mm |
| Depth | 129 mm |

Item dimensions with alternative mounting

PACT MCR-V2-10020-129-2000-1A1 - Current transformer



2905889

<https://www.phoenixcontact.com/us/products/2905889>

| | |
|--------|--------|
| Width | 129 mm |
| Height | 156 mm |
| Depth | 30 mm |

Copper rail

| | |
|--------|--------|
| Width | 100 mm |
| Height | 10 mm |

Copper rail 2

| | |
|--------|-------|
| Width | 80 mm |
| Height | 64 mm |

Circular conductor

| | |
|----------|-------|
| Diameter | 85 mm |
|----------|-------|

Material specifications

| | |
|------------------|--------|
| Housing material | PA 6.6 |
|------------------|--------|

Environmental and real-life conditions

Ambient conditions

| | |
|---|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 40 °C |
| Ambient temperature (storage/transport) | -25 °C ... 40 °C |
| Permissible humidity (operation) | Use only indoors, non-condensing |

Approvals

CE

| | |
|-------------|--------------|
| Certificate | CE-compliant |
|-------------|--------------|

UKCA

| | |
|-------------|----------------|
| Certificate | UKCA-compliant |
|-------------|----------------|

Standards and regulations

| | |
|-----------------------|----------|
| Standards/regulations | EN 61869 |
|-----------------------|----------|

PACT MCR-V2-10020-129-2000-1A1 - Current transformer



2905889

<https://www.phoenixcontact.com/us/products/2905889>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2905889>



EAC

Approval ID: RU*DE*08.B.01187/19

PACT MCR-V2-10020-129-2000-1A1 - Current transformer



2905889

<https://www.phoenixcontact.com/us/products/2905889>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27210902 |
| ECLASS-13.0 | 27210902 |
| ECLASS-12.0 | 27210902 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC002048 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121000 |
|-------------|----------|

PACT MCR-V2-10020-129-2000-1A1 - Current transformer



2905889

<https://www.phoenixcontact.com/us/products/2905889>

Environmental product compliance

| | |
|------------|--|
| China RoHS | Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |
|------------|--|

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com