



Polarizing Keys

In Between Contact & In Contact

ALL KEYS ORDERED SEPARATELY

IN BETWEEN CONTACT KEY
P/N: 04-0001-000
SULLINS PART: PLM-K1

Technical drawing showing a 3D perspective view and two 2D orthographic views (top and side) of the PLM-K1 key. Dimensions are: width $.200'' [5.08]$, height $.250'' [6.35]$, and thickness $.028'' [0.71]$.

IN CONTACT KEY
P/N: 04-0002-000
SULLINS PART: PLM-K2

Technical drawing showing a 3D perspective view and two 2D orthographic views (top and side) of the PLM-K2 key. Dimensions are: width $.235'' [5.97]$, height $.260'' [6.60]$, and thickness $.093'' [2.36]$.

IN BETWEEN CONTACT KEY
P/N: 04-0003-000
SULLINS PART: PLA-K1

Technical drawing showing a 3D perspective view and two 2D orthographic views (top and side) of the PLA-K1 key. Dimensions are: width $.230'' [5.84]$, height $.200'' [5.08]$, and thickness $.030'' [0.76]$.

IN BETWEEN CONTACT KEY
P/N: 04-0004-000
SULLINS PART: PLC-K1

Technical drawing showing a 3D perspective view and two 2D orthographic views (top and side) of the PLC-K1 key. Dimensions are: width $.100'' [2.54]$, height $.285'' [7.24]$, and thickness $.038'' [0.97]$.

Micro Plastics Brand Card Edge