


## General information

|                   |                     |
|-------------------|---------------------|
| Part number       | GK1YDR-P05UJ00-000L |
| Termination       | pcb                 |
| Size              | 1                   |
| Locking principle | break , push        |
| Coding            | d_key_amc           |
| Cable Diameter    | cable_amc_1         |



## Contact insert description

|                      |         |
|----------------------|---------|
| Number of contacts   | 5       |
| Contact type         | sockets |
| Contact diameter     | 09mm    |
| Insulator material   | peek    |
| Termination          | pcb     |
| Termination diameter | 07mm    |

reverse\_gender\_on\_request

## Technical information

|                                |           |               |
|--------------------------------|-----------|---------------|
| Nominal current single contact | 07_a      | iec_60512_5_2 |
| Nominal current insert         | 5,25 A    | vde_0298_4    |
| Test voltage                   | 135_kv_ac | eia_364_20f   |

safety\_text

## Mechanical and environmental data

|                       |              |
|-----------------------|--------------|
| Degree of protection* | ipsk8_ip6k9k |
| Operating temperature | 51_125_c     |
| Mating cycles         | 5000         |

mated

## Material and surface treatments

|                |               |
|----------------|---------------|
| <b>Housing</b> | ruthenium     |
| <b>Contact</b> | cu_alloy_gold |

safety\_text\_2  
ul\_text  
illustrative\_text