

United States [Change]

Q

• Print

United States > Government Solutions > All 3M Products > Consumer > Home Improvement > Painting Supplies > Masking Tape > Scotch® Masking Tape for Hard-to-Stick Surfaces 2060-36A-BK Green, 36 mm x 55 m, 24 per case Bulk

Scotch® Masking Tape for Hard-to-Stick Surfaces 2060-36A-BK Green, 36 mm x 55 m, 24 per case Bulk

3M ID 70071202876 UPC# 00021200720673 CAT# 2060-36A-BK

Where to Buy Like Sign Up to see what your friends like. verview Image: Sign Up to see what your friends like. cotch@ Masking Tape for Hard-to-Stick Surfaces 2060 is for rough, non-damageable surfaces. This tape provides exceptional durability and staying power, yet amoves cleanly. Bond aggressively, yet has a smooth unwind. specifications Image: Sign Up to see what your friends like. Adhesion Strength Very High Color Green Length 55 m Recommended Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick				• 111
surfaces such as stucco, concrete and brick. Questions? We can help Contact Us sorfaces such as stucco, concrete, rough wood and stucco 3-Day clean removal Can be used with lacquer coatings Very High Adhesion level Uhere to Buy Like Sign Up to see what your friends like. strates strate			very high adhesion and is designed for use with lacquer	Need Help? • Sh
 For use on brick, concrete, rough wood and stucco 3-Day clean removal Can be used with lacquer coatings Very High Adhesion level Where to Buy Like Sign Up to see what your friends like. cockh@ Masking Tape for Hard-to-Stick Surfaces 2060 is for rough, non-damageable surfaces. This tape provides exceptional durability and staying power, yet moves cleanly. Bond aggressively, yet has a smooth unwind. pecifications Adhesion Strength Very High Color Green Length 55 m Recommended Surfaces Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Surfaces Burks, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Removal Time 3 day removal Tickness 0.006 Inch UV Resistant No	Scotch Masking Tape	Hard-to-Stick		
 Can be used with lacquer coatings Very High Adhesion level Where to Buy Like Sign Up to see what your friends like. verview cotch® Masking Tape for Har-t-o-Stick Surfaces 2060 is for rough, non-damageable surfaces. This tape provides exceptional durability and staying power, yet mass as smooth unwide. pedifications pedifications color Green Length S n Goor Green Ling Sin L Color Green Length S fon Recommended Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Surfaces Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Grades Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Brick, Concrete,	Entrance Dressbyrg		 For use on brick, concrete, rough wood and stucco 	Contact Us
 Very High Adhesion level Where to Buy Like Sign Up to see what your friends like. 			3-Day clean removal	
 Very High Adhesion level Where to Buy Like Sign Up to see what your friends like. verview verview Adhesion Strength Very High Adhesion Strength Very High Verview Very High Adhesion Strength Very High Golor Green Length 55 m Recommended surfaces Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Removal Time 3 day removal Tickness 0.06 Inch UV Resistant No			Can be used with lacquer coatings	
Like Sign Up to see what your friends like. verview Code Gene Length Sin Recommended Sin Concrete, Grout, Lacquer applications, Other rough or hard-to-stick surfaces Removal Time 3 day removal Thickness Outo Ench UV Resistant Versistant Versistant Versistant Versistant Sign Up to see what your friends like. 	-		Very High Adhesion level	
verview cotch® Masking Tape for Hard-to-Stick Surfaces 2060 is for rough, non-damageable surfaces. This tape provides exceptional durability and staying power, yet emoves cleanly. Bond aggressively, yet has a smooth unwind. cotch® Masking Tape for Hard-to-Stick Surfaces 2060 is for rough, non-damageable surfaces. This tape provides exceptional durability and staying power, yet emoves cleanly. Bond aggressively, yet has a smooth unwind. cotch @ Green Green Length 55 m Recommended surfaces Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick surfaces reader 3 day removal Thickness 0.006 Inch UV Resistant No			Where to Buy	
Scotch® Masking Tape for Hard-to-Stick Surfaces 2060 is for rough, non-damageable surfaces. This tape provides exceptional durability and staying power, yet emoves cleanly. Bond aggressively, yet has a smooth unwind. Specifications Adhesion Strength Very High Color Green Length 55 m Recommended Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick surfaces surfaces 3 day removal Thickness 0.006 Inch UV Resistant No			Like Sign Up to see what your friends like.	
ColorGreenLength55 mRecommended surfacesBrick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick surfacesRemoval Time3 day removalThickness0.006 InchUV ResistantNo				
Adhesion Strength Very High Color Green Length 55 m Recommended surfaces Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick surfaces Removal Time 3 day removal UV Resistant No				
ColorGreenLength55 mRecommended SurfacesBrick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick surfacesRemoval Time3 day removalThickness0.006 InchUV ResistantNo	cotch® Masking Tape for			urability and staying power, yet
Length55 mRecommended SurfacesBrick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick surfacesRemoval Time3 day removalThickness0.006 InchUV ResistantNo	cotch® Masking Tape for moves cleanly. Bond agg pecifications	ressively, yet has a smooth		urability and staying power, yet
Recommended Brick, Concrete, Grout, Lacquer applications, Other rough or hard-to-stick Surfaces Surfaces Removal Time 3 day removal Thickness 0.006 Inch UV Resistant No	cotch® Masking Tape for moves cleanly. Bond agg pecifications Adhesion Strength	ressively, yet has a smooth Very High		urability and staying power, yet
Surfaces surfaces Removal Time 3 day removal Thickness 0.006 Inch UV Resistant No	cotch® Masking Tape for moves cleanly. Bond agg pecifications Adhesion Strength Color	rressively, yet has a smooth Very High Green		urability and staying power, yet
Thickness 0.006 Inch UV Resistant No	cotch® Masking Tape for moves cleanly. Bond agg pecifications Adhesion Strength Color Length	ressively, yet has a smooth Very High Green 55 m	h unwind.	urability and staying power, yet
UV Resistant No	cotch® Masking Tape for moves cleanly. Bond agg pecifications Adhesion Strength Color Length Recommended	rressively, yet has a smooth Very High Green 55 m Brick, Concrete, Grout	h unwind.	urability and staying power, yet
	cotch® Masking Tape for moves cleanly. Bond agg pecifications Adhesion Strength Color Length Recommended Surfaces	ressively, yet has a smooth Very High Green 55 m Brick, Concrete, Grout surfaces	h unwind.	urability and staying power, yet
Width 36 mm	cotch® Masking Tape for moves cleanly. Bond agg pecifications Adhesion Strength Color Length Recommended Surfaces Removal Time	ressively, yet has a smooth Very High Green 55 m Brick, Concrete, Grout surfaces 3 day removal	h unwind.	urability and staying power, yet
	cotch® Masking Tape for moves cleanly. Bond agg pecifications Adhesion Strength Color Length Recommended Surfaces Removal Time Thickness	ressively, yet has a smooth Very High Green 55 m Brick, Concrete, Grout surfaces 3 day removal 0.006 Inch	h unwind.	urability and staying power, yet

3M: News | Careers | Partners & Suppliers | Investor Relations | SDS Search | Transport Information Search | Help Center

Legal Information Privacy Policy

© 3M 2015. All Rights Reserved.

