

## NFS110 Medical Series

Single and quad output

### Data Sheet


**Total Power: 80 - 110 W**  
**Input Voltage: 100 - 240Vac**  
**127 - 357 Vdc**  
**# of Outputs: Single, quad**

### SPECIAL FEATURES

- 7.0 x 4.25 x 1.8 inch package
- Medical, dental and laboratory applications
- Overshoot and short circuit protection
- 110 W with 20 CFM
- UL, cUL and VDE approvals
- EN60601-1 and UL2601 medical approvals
- Available RoHS compliant
- 2 years warranty

### SAFETY

- EN60950-1/IEC60950-1
- EN60601-1
- UL60601-1/CSA C22.2 No. 601-1 File No. E182560



### Electrical Specifications

Output		
Voltage adjustability:	+5.1 V o/p on multi's 5.1 V single output 12 V single output 15 V single output 24 V single output	± 3.0% ± 3.0% 12 - 14 V 15 - 18 V 24 - 30 V
Line regulation:	LL to HL, FL All outputs on all units	± 0.1% max.
Overshoot/undershoot:	At turn-on no lead	0%
Temperature coefficient:	All outputs	±0.02% / °C
Overshoot protection:	Multi o/p 5.1 V only 5.1 V single 12 V single 15 V single 24 V single	6.25 V ± 0.75 V 6.25 V ± 0.75 V 15.75 V ± 1.0 V 22 V ± 1.5 V 33 V ± 2.5 V
Output power limit:	Primary power limited	Pin max. 160 W Pout min. 110 W
Short circuit protection:		Burst mode operation
Input		
Input voltage range:		100 - 240 Vac 127 - 357 Vdc
Input frequency range:		47 - 440 Hz
Input surge current:	110 Vac. 50 Hz 230 Vac. 50 Hz	17 A 25 A
Safety ground leakage current:	132 Vac 264 Vac	50 µA 100 µA

All specifications are typical at nominal input, full load at 25 °C unless otherwise stated

### EMC Characteristics

Conducted emissions:	EN55022, FCC part 15	Level A
Radiated emissions:	EN55022, FCC part 15	Level A
ESD air:	EN61000-4-2, level 3	Perf. criteria 1
ESD contact:	EN61000-4-2, level 4	Perf. criteria 1
Surge:	EN61000-4-3, level 3	Perf. criteria 1
Fast transients:	EN61000-4-4, level 3	Perf. criteria 1
Radiated immunity:	EN61000-4-5, level 3	Perf. criteria 2
Conducted immunity:	EN61000-4-6, level 3	Perf. criteria 2

### General Specifications

Hold-up time:	110 Vac @ 80 W 110 Vac @ 110 W 230 Vac @ 80 W 230 Vac @ 110 W	35 ms 17 ms 140 ms 100 ms
Efficiency:	Multiple outputs +5.1 V single 12 V and 15 V singles 24 V single	70% typical 70% typical 72% typical 75% typical
Isolation voltage:	Input/output Input/chassis	4000 Vac 1500 Vac
Approvals and standards: (see note 12)		VDE0750, IEC60601, IEC1010, UL60601, CSA C22.2 No. 125
Weight:	Singles Multiple outputs	550 g (19.4 oz) 600 g (21.2 oz)
MTBF (@25 °C)	MIL-HDBK-217E	125,000 hours min.

### Environmental Specifications

Thermal performance:	Operating, see curve	0°C to +70°C
(See notes 9, 10)	Non-operating	-40°C to +85°C
	0 °C to 50 °C amb. convection cooled	80 W
	+50 °C to +70 °C, amb. convection cooled	Derate 2 W/°C
	0 °C to +50 °C, 20 CFM forced air	110 W
	+50 °C to +70 °C, 20CFM forced air	Derate 2.75 W/°C
Relative humidity:	Peak, 0 °C to +50 °C, max. 60 seconds	110W
Altitude:	Non-condensing	5% to 95% RH
	Operating	10,000 feet max.
	Non-operating	40,000 feet max.
Vibration (See Note 11):	5-500 Hz	2.4 G rms peak

### Ordering Information

Output Voltage	Output Currents			Ripple <sup>(4)</sup>	Total Regulation <sup>(5)</sup>	Model Numbers <sup>(13, 14, F)</sup>
	Max <sup>(1)</sup>	Peak <sup>(2)</sup>	Fan <sup>(3)</sup>			
+5.1 V	8 A	20 A	10 A	50 mV	± 2.0%	NFS110-7901PJ
+12 V	4.5 A	9 A	5 A	120 mV	± 3.0%	
-12 V	0.5 A	1.5 A	1 A	120 mV	± 3.0%	
-5 V	0.5 A	1.5 A	1 A	50 mV	± 3.0%	
+5.1 V ( $I_A$ )	8 A	20 A	10 A	50 mV	+ 2.0%	NFS110-7902PJ
+24 V ( $I_B$ ) <sup>(6)</sup>	3.5 A	4.5 A	4.5 A	240 mV	+ 10 / - 5.0%	
+12 V	4.5 A	9 A	5 A	120 mV	± 3.0%	
-12 V	0.5 A	1.5 A	1 A	120 mV	± 3.0%	
12 V	7 A	9 A	9 A	120 mV	± 2.0%	NFS110-7912J <sup>(7,8)</sup>
15 V	5 A	7.3 A	7.3 A	150 mV	± 2.0%	NFS110-7915J <sup>(7,8)</sup>
24 V	3.5 A	4.5 A	4.5 A	240 mV	± 2.0%	NFS110-7924J <sup>(7,8)</sup>

### Transient Response


NFS110-7901PJ	+5.1 V (7.5-10 A)	150 mV peak, 1 ms recovery
	+12 V (2.5-5 A)	100 mV peak, 0.5 ms recovery
	-12 V (0.5-1 A)	100 mV peak, 0.5 ms recovery
	-5 V (0.5-1 A)	100 mV peak, 0.5 ms recovery
NFS110-7902PJ	+5.1 V (7.5-10 A)	150 mV peak, 1 ms recovery
	+12 V (2.5-5 A)	100 mV peak, 0.5 ms recovery
	-12 V (0.5-1 A)	100 mV peak, 0.5 ms recovery
	24 V (1.5-3 A)	300 mV peak, 1 ms recovery
NFS110-7905J	+5.1 V (10-20 A)	250 mV peak, 1 ms recovery
NFS110-7912J	+12 V (4.5-9 A)	360 mV peak, 1 ms recovery
NFS110-7915J	+15 V (3.65-7.3 A)	450 mV peak, 1 ms recovery
NFS110-7924J	+24 V (2.25-4.5 A)	720 mV peak, 1 ms recovery

### Notes



- Convection cooled, 80 W maximum.
- Peak outputs lasting less than 60 seconds with duty cycle less than 10%. Total peak power must not exceed 110 W.
- Forced air, 20 CFM at 1 atmosphere, 110 W maximum.
- Figure is peak-to-peak. Output ripple is measured across a 50 MHz bandwidth using a 12 inch twisted pair terminated with a 47  $\mu$ F capacitor.
- Total regulation is defined at the static output regulation at 25 °C, including initial tolerance, line voltage within stated limits and output voltages adjusted to their factory settings. Also for NFS110-7902PJ, for 24 V output stated regulation  $I_A / I_B \leq 5$ . This output will maintain  $\pm 5.0\%$  regulation if  $I_A \leq 5$  A, where  $I_A = +5.1$  V output current and  $I_B = +24$  V output current.
- Single output models have floating outputs which may be referenced as either positive or negative. Higher voltage supplies, may be adjusted over a wide output voltage range, as long as the total output power does not exceed 80 Watts (natural convection) or 110 Watts (forced air).
- Power fail detect not available on single output models.
- Derating curve is application specific for ambient temperatures > 50 °C, for optimum reliability no part of the heatsink should exceed 90 °C and no semiconductor case temperature should exceed 100 °C.
- Caution: Allow a minimum of 1 second after disconnecting the power when making thermal measurements.
- The user should read the PSU installation instructions in conjunction with the relevant national safety regulations in order to ensure compliance.
- Three orthogonal axes, random vibration, 10 minute test for each axis.
- This product is only for inclusion by professional installers within other equipment and must not be operated as a stand alone product.
- The 'J' suffix indicates that these parts are Pb-free (RoHS 6/6) compliant. TSE RoHS 5/6 (non Pb-free) compliant versions may be available on special request, please contact your local sales representative for details.
- NOTICE: Some models do not support all options. Please contact your local Artesyn Embedded Technologies representative or use the on-line model number search tool at [www.artesyn.com/power](http://www.artesyn.com/power) to find a suitable alternative.

AC (J1) mating connector  
 Molex 09-50-3051 or Molex 09-91-0500 mating connector  
 with 2478 or equivalent crimp terminals.

DC (J2) mating connector  
 Molex 09-50-3131 or Molex 09-91-1300 mating connector  
 with 2478 or equivalent crimp terminals.



Power fail detect signal (Note 8)  
 $50 \text{ ms} \leq T1 \leq 200 \text{ ms}$   
 $T2$  will vary with line and load  
 $T3 \geq 3 \text{ ms}$   
 $P_{out}: 110 \text{ W}$   
 PFD output is an open collector which will sink  $\leq 40 \text{ mA}$  in the low state.



**Mechanical Notes**

- A Metallic or non-metallic stand-offs (maximum diameter 5.4 mm) can be used in all four mounting holes without effecting safety approval.
- B The ground pad of the mounting hole near J1, allows system grounding through a metal stand-off to the system chassis.
- C The heat sink is grounded, and allows system grounding by mechanical connection to the system chassis.
- D The supply must be mechanically supported using the PCB mounting holes and may be additionally supported by the heatsink mounting holes.
- E It is always advisable to attach the power supply heat sink to another thermal dissipator (such as a chassis or finned heatsink etc). The resulting decrease in heat sink mounted component temperatures will improve power supply lifetime.
- F A standard L-bracket and cover is available for mounting which contains all screws, connectors and necessary mounting hardware. The kit is available, order part number "NFS110CJ".



Pin Connections			
J1	-7901PJ	-7902PJ	SINGLES
Pin 1	AC Ground	AC Ground	AC Ground
Pin 2	AC Neutral	AC Neutral	AC Neutral
Pin 3	AC Line	AC Line	AC Line
J2			
Pin 1	+5.1 V	+5.1 V	V <sub>out</sub>
Pin 2	+5.1 V	+5.1 V	V <sub>out</sub>
Pin 3	+5.1 V	+5.1 V	V <sub>out</sub>
Pin 4	Return	Return	Return
Pin 5	Return	Return	Return
Pin 6	Return	Return	Return
Pin 7	Return	Return	Return
Pin 8	+12 V	+12 V	V <sub>out</sub>
Pin 9	+12 V	+12 V	V <sub>out</sub>
Pin 10	PFD	PFD	N/C
Pin 11	-12 V	-12 V	N/C
Pin 12	Removed for Key		
Pin 13	-5 V	+24 V	N/C

N/C = no connection.

## WORLDWIDE OFFICES

### Americas

2900 S.Diablo Way  
 Tempe, AZ 85282  
 USA  
 +1 888 412 7832

### Europe (UK)

Waterfront Business Park  
 Merry Hill, Dudley  
 West Midlands, DY5 1LX  
 United Kingdom  
 +44 (0) 1384 842 211

### Asia (HK)

14/F, Lu Plaza  
 2 Wing Yip Street  
 Kwun Tong, Kowloon  
 Hong Kong  
 +852 2176 3333



[www.artesyn.com](http://www.artesyn.com)

While every precaution has been taken to ensure accuracy and completeness in this literature, Artesyn Embedded Technologies assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions. Artesyn Embedded Technologies, Artesyn and the Artesyn Embedded Technologies logo are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners.  
 © 2014 Artesyn Embedded Technologies, Inc.

For more information: [www.artesyn.com/power](http://www.artesyn.com/power)  
 For support: [productsupport.ep@artesyn.com](mailto:productsupport.ep@artesyn.com)