



- NOTES:**
- METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
 - INSULATORS: PBT GF UL 94 V-0; BLACK
 - CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):
 - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
 - PLEASE ADD B for 20µm HARD GOLD over min. 50µm NICKEL
 - PLEASE ADD C for 30µm HARD GOLD over min. 50µm NICKEL
 - THREADED REAR SPACERS / FRONT THREADED LOCKS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
 - SLEEVES: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
 - MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
 - CONNECTOR IS PART MARKED: 163□13739X CONEC ABC (see note 3)

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale: 2:1 (5:1)	material: SEE NOTES
	drawn	11.03.02	Schmidt		title: D-SUB MALE 15pos. SOLDER PIN STRAIGHT with threaded rear spacer / front threaded lock	
	appd.	11.03.02	Mickenbecker			
	norm					
	2 x b	A5226	27.05.2014	K.H.	dwg no:	16K1A657
a	Original			part no:	(b)163□13739X (see note 3)	sh: 1

Directive 2002/95/EC RoHS compliant

