

Residential Combustion Meter



C160

Entry Level Combustion Meter Easy To Use And Rugged Design







FREE SHIPPING

Functions • Measures: 02 , Flue Temperature,

- Inlet TemperatureCalculates: CO2, Losses, Efficiency
- Calculates: CO2, Losses, Efficienc (Net, Gross), Excess Air

Features

- Backed by UEi Service+
- Up to 10-Year warranty with annual recertification
- Large 6-line backlit display
- Low Flow Detection to protect reading accuracy
- Entry level combustion meter
- High altitude compensation
- Protective water trap
- 8 pre-programmed fuels
- Protective rubber boot with magnets
- DMM-style rotary dial
- 30 memory positions

Applications

Installation and maintenance of furnaces and boilers to optimize efficiency, reduce fuel costs



Includes

- Flue Probe (CP2)
- Rechargeable Batteries (AA)
- USB Charging cable (AACA5)
- Quick Start Guide (201991)



USA 1.800.547.5740 CANADA 1.877.475.0648





Specifications

Temperature Measurement

| | Range | Resolution | Accuracy |
|------------------|-----------------------------|---------------|--------------------------|
| Flue Temperature | 32° to 1112°F (0° to 600°C) | 0.2°F (0.1°C) | ±(0.3% rdg +3.6°F (2°C)) |

Flue Gas Measurement

| | Range | Resolution | Accuracy |
|--------|------------|------------|--------------|
| Oxygen | 0 to 20.9% | 0.10% | ±0.3% Volume |

Calculations

| | Range | Resolution | Accuracy |
|---------------------|------------|------------|------------|
| Carbon Dioxide | 0 to 30% | 1.00% | ±0.3% rdg |
| Efficiency | 0 to 99.9% | 0.10% | ±1.0% rdg |
| Excess Air | 0 to 250% | 0.10% | ±0.2% rdg |
| Efficiency High (C) | 0 - 119.9% | 0.1% | ±1% of rdg |

| Pre P | rogrammed | Fuels |
|-------|-----------|-------|

Natural Gas, Propane, LPG, Light Oil, Heavy Oil, Bio Oil, Pellets

| Battery Life | >8 hours (continuous with pump on) | |
|--------------|------------------------------------|--|
|--------------|------------------------------------|--|

Operating Conditions

| Temperature | 32 to 113°F (0 to 45°C) | |
|--------------|--------------------------------------|--|
| Humidity | 15 to 90% R.H. (non-condensing) | |
| Power Supply | Rechargeable Batteries, USB charging | |



WWW.UEITEST.COM