Line Voltage Auxiliary Relays

POWER PACKS AND RELAYS





RRU

PRODUCT FEATURES

- 120 or 277VAC models available
- 20 Amp switching capacity
- N.O. isolated contact
- UL and cUL listed
- Five-year warranty

General Spec

eral Specifications		
Electrical Ratings	RRU120 – 2400 watts @ 120VAC 50/60 Hz, 1 HP RRU277 – 5000 watts @ 277VAC 50/60 Hz, 1.5 HP	
Operating environment	Indoor use only	
Dimensions	2.75" W x 4.5" L x 1.10" D (69.85mm W 114.3mm L 27.94mm D)	
Weight	3.0 oz. (85.05g)	
Color	White	
Certifications	UL and cUL Listed	
Warranty	Five years	

Ordering Information

HUBBELL®

Control Solutions

MODEL		
RRU120 Auxiliary Relay for 120V Line Voltage Sensors		
RRU277 Auxiliary Relay for 277V Line Voltage Sensors		



PROJECT INFORMATION Project Name

Catalog No.

Date

Our remote relay units (RRU) are used to switch additional lighting or other control circuits. Designed to work with line voltage sensors, the RRU provides 20 amp switching capacity and features a Normally Open (N/O) isolated contact.



701 Millennium Blvd. | Greenville, SC 29607 | 864-678-1000 | 866-898-0131 fax | www.hubbellcontrolsolutions.com Copyright © 2017 Hubbell Control Solutions, a division of Hubbell Lighting, Inc. Subject to change without notice. Trademarks are property of their respective owners.

1605A 4.6.17