


Monitor - VL FPM 19U - 2913021

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



15-in. display shown

Key commercial data

| | |
|------------------------|--|
| Packing unit | 0 |
| Minimum order quantity | 1 |
| GTIN |  4 046356 662321 |
| Custom tariff number | 85285100 |
| Country of origin | TAIWAN |

Technical data

Display data

| | |
|------------------------|-----------------------------------|
| Display | 48.3 cm/19" TFT active |
| Resolution | 1280 x 1024 Pixel (SXGA) |
| Backlighting | CCFL |
| Display backlight MTBF | > 50000 h |
| Touch screen | Resistive industrial touch screen |
| Colors | 16.7 million |

Computer data

| | |
|-------------------|--------------------------|
| Processor | without |
| Main memory | without |
| Processor fan | Without fan |
| Data memory | without |
| Interfaces | 1x DVI-D, 1x VGA, 3x USB |
| Network | without |
| Operating systems | No operating system |
| Slots | without |
| Power supply unit | 24 V DC +/- 20% |

General data

| | |
|--------------------------------|--------|
| Installation dimension, width | 444 mm |
| Installation dimension, height | 362 mm |

Monitor - VL FPM 19U - 2913021

Technical data

General data

| | |
|---------------------------------------|----------------------------|
| Note regarding installation dimension | Panel cutout |
| Mounting type | Panel cutout or VESA mount |
| Weight | 9.51 kg |

Ambient Conditions

| | |
|--|--|
| Degree of protection | IP65 (front), IP20 (back) |
| Ambient temperature (operation) | 0 °C ... 55 °C |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Permissible humidity (operation) | 5 % ... 95 % |
| Permissible humidity (storage/transport) | 5 % ... 95 % |
| Vibration (operation) | DIN EN 60068-2-6 |
| Shock | 15g, 11 ms in accordance with IEC 60068-2-27 |

Classifications

eclass

| | |
|------------|----------|
| eCl@ss 5.1 | 27242301 |
| eCl@ss 6.0 | 27242301 |
| eCl@ss 7.0 | 27242301 |

etim

| | |
|----------|----------|
| ETIM 4.0 | EC001413 |
|----------|----------|