

M23 P КОНТАКТ 2mm (0,75–2,5mm²) Au



Image is for illustration purposes only. Please refer to product description.

Part number	09 15 600 6121
Specification	M23 P КОНТАКТ 2mm (0,75–2,5mm ²) Au
HARTING eCatalogue	https://b2b.harting.com/09156006121

Version

Gender	Male
Manufacturing process	Turned contacts

Technical characteristics

Conductor cross-section	0.75 ... 2.5 mm ²
Operating current	≤28 A
Contact resistance	≤3 mΩ
Stripping length	7 mm

Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Gold plated
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	339476a1-86ba-49e9-ab4b-cd336420d72a
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead



Pushing Performance
Since 1945

Material properties

Fire protection on railway vehicles EN 45545-2 (2020-08)

Requirement set with Hazard Levels R26

Specifications and approvals

Specifications IEC 60664-1
IEC 61984

Commercial data

Packaging size 100

Net weight 0.1 g

Country of origin Germany

European customs tariff number 85366990

GTIN 5713140189010

eCl@ss 27440204 Contact for industrial connectors