



11	ID LABEL	POLYPROPYLENE	CLEAR, (LABEL DETAIL)
10	OVERMOLD	TPE	SEE P/N CHART
9	SOCKET CONTACT	Cu ALLOY	GOLD PLATED
8	WIRE, 18AWG (UL1015)	PVC INSULATION	SEE FACE VIEWS
7	FEMALE COUPLING	ZINC DIE-CAST	BLACK E-COAT
6	FRICITION RING	NYLON	WHITE
5	FEMALE INSERT	TPE	SEE P/N CHART
4	MALE COUPLING	ZINC DIE-CAST	BLACK E-COAT
3	M/F CONTACT (GROUND)	Cu ALLOY	GOLD PLATED
2	M/F CONTACT (SIGNAL)	Cu ALLOY	GOLD PLATED
1	MALE INSERT	TPE	SEE P/N CHART
ITEM	DESCRIPTION	MATERIAL	FINISH

- (A) NOTES:
1. MATERIAL: AS NOTED
  2. FINISH: AS NOTED
  3. ELECTRICAL:  
VOLTAGE: 483V PER IEC60664  
600V PER UL2238  
CURRENT: 10A
  4. TEMP RATING: -20°C TO +80°C
  5. PROTECTION: IP67 (WHEN MATED)
  6. COUPLING THREADS: 7/8-16UN
  7. UL LISTED FILE: E152210
  8. ALL DIMS ARE FOR REFERENCE UNLESS TOLERANCED OR NOTED OTHERWISE

1300350115	DNETAUXPTG	BLACK	WHITE
1300350085	DNETAUXPT	YELLOW	BLACK
PART NO.	ENG. NO.	O-MOLD & INSERT COLOR	LABEL PRINT COLOR

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

FUNCTIONAL SYMBOLS: FA=0, FE=0, FE=0

DIVISIONAL SYMBOLS: 4 PLACES ±, 3 PLACES ±, 2 PLACES ±, 1 PLACE ±, 0 PLACES ±

ANGULAR TOL ± °

SCALE: INCH 2:1

GENERAL TOLERANCES (UNLESS SPECIFIED): MM, INCH

CURRENT REV DESC: REDRAW TO NX, ADD BOM TABLE, UPDATE NOTES, REMOVE CENEL, ORIENT VIEWS TO MATCH MFG DOC

EC NO: 701309  
DRWN: RSTONE 2022/03/14  
CHK'D: MZIELINSKI 2022/03/29  
APPR: BWOODMAN 2022/04/11

INITIAL REVISION:  
DRWN: DRWN BY 0099/99/99  
APPR: APPR BY 0099/99/99

THIRD ANGLE PROJECTION

DRAWING C-SIZE

SERIES 130035

MOLEX

MINI-CHANGE TEE  
4 POLE MALE/FEM TRUNK, 4 POLE FEMALE DROP  
SINGLE KEY

PRODUCT CUSTOMER DRAWING

DOCUMENT NUMBER: 1300350085  
DOC TYPE: PSD  
DOC PART: 000  
REVISION: A

MATERIAL NUMBER: CUSTOMER: SHEET NUMBER: 1 OF 1