



- NOTES: (b)
- METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
 - INSULATORS: PBT GF UL 94 V-0; BLACK
 - CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):
 - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
 - PLEASE ADD B for 20µm HARD GOLD over min. 50µm NICKEL
 - PLEASE ADD C for 30µm HARD GOLD over min. 50µm NICKEL
 - THREADED REAR SPACERS/FRONT THREADED LOCKS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
 - SLEEVES: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
 - MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
 - CONNECTOR IS PART MARKED: 163□14449X CONEC ABC (see note 3)

RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale:	2:1 (5:1)		
					material:	SEE NOTES		
			date	name		title:		
			drawn	29.09.2015 M.Heinrich		D-SUB MALE 15pos. SOLDER PIN STRAIGHT with threaded rear spacer/front threaded lock		
			appd.	29.09.2015 Lehmenkühler				
			norm					
			d-old	16K1A1729		dwg no:		
4 x b	Ä5835	29.09.15	Heinrich			16K1A3718 (b) DIN-A3 sh: 1		
a	Original					part no: (b) 163□14449X (see note 3)		