Insulation stop; 0.75 - 1 mm<sup>2</sup>; 5 pieces/strip; black

www.wago.com/280-472



Color:
COIOI.

Data
Connection data

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$ 

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com

www.wago.com/280-472



### Connection 1

Strip length 8 ... 9 mm / 0.31 ... 0.35 inches

# **Material Data**

Note (material data)

Information on material specifications can be found here

Color	black
Fire load	0.008 MJ
Weight	0.3 g

#### Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	200 (25) pcs
Packaging type	box
Country of origin	DE
GTIN	4017332267328
Customs tariff number	39269097900

### **Environmental Product Compliance**

RoHS Compliance Status Compliant, No Exemption

#### **Downloads**

### Documentation

#### **Bid Text**

280-472 X81 - Datei	2019 年2月19日	xml 2.6 kB	Download
280-472 doc - Datei	2018 年1月4日	doc 24.1 kB	Download

# **Additional Information**

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/280-472



pdf 2.3 MB Download

## CAD/CAE-Data

CAD data

2D/3D Models 280-472 URL Download

**CAE** data WSCAD Universe 280-472 URL Download **URL** Download ZUKEN Portal 280-472 URL EPLAN Data Portal 280-472 Download

**Environmental Product Compliance** 

Compliance Search

Environmental Product Compliance 280-472 URL Download Insulation stop; 0.75 - 1 mm<sup>2</sup>; 5 pieces/strip; black

### **Installation Notes**

Installation

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com

www.wago.com/280-472



The problem: Wiring programmable logic controllers and microprocessor-operated control circuits often relies on very small, finestranded conductors. These conductors are highly flexible and deform when pushed against the conductor stop in terminal blocks. As a result, the conductor insulation – not the copper conductor – may be clamped, causing intermittent contact or no contact at all. Common to all terminal block types currently offered, this problem creates unnecessary downtime for troubleshooting.

The solution: An insulation stop for rail-mount terminal blocks. Insulation stops automatically bundle the cores of fine-stranded conductors when inserted into the clamping unit, preventing splaying. This also limits the conductor entry to a defined cross sectional area – ensuring the actual conductor, not the insulation, will enter the clamping unit.

Insulation stops are available as dividable 5-pole strips for 279, 280/780/870/880 and 281 /781 Series Rail-Mount Terminal Blocks.

Insulation stop usage will not affect the conductor strip lengths for the aforementioned rail-mount terminal blocks.

Conductor termination

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com

www.wago.com/280-472



Insert stripped, untwisted conductor into insulation stop.	The conductor is bundled.

The conductor insulation is prevented from being pushed into the clamping unit by the positive stop.

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$ 

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com