

Solder Cups

Material and Finish

- Shell: steel, nickel plated
- Insulator: PBT with glass-fiber reinforcement, UL 94V-0 rated, color-black
- Contact Material:
 - Socket: Brass
- Contact Plating:
- Standard:
 - Gold flash on mating end, tin on termination end, with entire contact nickel underplated
- 15 Option:
 - 15u" gold on mating end, tin on termination end, with entire contact nickel underplated
- 30 Option:
 - 30u" gold on mating end, tin on termination end, with entire contact nickel underplated

Electrical Specifications

- Rated Current: 2A
- Rated Voltage: 30V RMS
- Withstanding Voltage: 500V (rms) AC for 1 minute
- Insulation Resistance: more than 1000 Megohm at 500V DC
- Contact Resistance: 13 milliohm max.
- Dielectric Strength: 1000V for 1 minute
- Operating Temperature: -55°C to +105°C

Part Number	Contact Area Plating Finish
K85X-BA-25S-R	Gold Flash (standard)
K85X-BA-25S-R15	15u" Gold (15 option)
K85X-BA-25S-R30	30u" Gold (30 option)




Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	05/20/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	05/20/05
A2	1/8/08	ECO # 07-052	WILL H.	H. MA		
A3	12/31/17	ECO #17-030	J. Elbanna	C. Furumasu		

K85X-BA-25S-R

Solder Cup D-Sub, RoHS Compliant
25 Pin Female, Round Riveted Jackscrews



UNITS
mm