

## 3M™ Dual Conductor Fabric Wrist Band for Monitors 2368, 2368VM

The Dual Conductor Fabric Wrist Bands are available in one size that adjusts to most any size wrist to provide reliable protection. The wrist band provides full conductivity, comfort and reliability, while ensuring continuous drain of static charge when used with the 3M™ Dual Conductor Cords 2300 Series. Meets the wrist band requirements of ANSI/ESD S20.20-2014.



**! WARNING:**  
All 3M Wrist Straps should not be used in areas where the individual may come in contact with electrical circuitry exceeding 250 volts.

### Specifications - Band

|                    |                          |
|--------------------|--------------------------|
| Fabric             | Elastic, Nylon           |
| Contact            | 360 degrees around wrist |
| Color              | Turquoise                |
| Plug Size          | 3.4 mm                   |
| Cord Removal Force | < 5 lbs.                 |

### Part Numbers

|        |   |
|--------|---|
| 2368   | 3M™ Dual Conductor Adjustable Fabric Wrist Band 2368, Turquoise         |
| 2368VM | 3M™ Dual Conductor Adjustable Fabric Wrist Band 2368VM (790 only), Gray |

### Related Products

- 3M™ Dual Conductor Coiled Cord 2360, 5 ft. (1.5 m) practical length
- 3M™ Dual Conductor Coiled Cord 2370, 10 ft. (3.0 m) practical length
- 3M™ Dual Conductor Coiled Cord 2371, 20 ft. (6.1 m) practical length
- 3M™ Dual Conductor Coiled Cord 2360R, 5ft. (1.5 m) practical length, with right angle mono plug connection ( to be used only with 3M monitors)
- 3M™ Dual Conductor Coiled Cord 2370R, 10 ft. (3.0 m) practical length, with right angle mono plug connection ( to be used only with 3M monitors)
- 3M™ Dual Conductor Coiled Cord 2371R, 20 ft. (6.1 m) practical length, with right angle mono plug connection ( to be used only with 3M monitors)

\*Meets the wrist band requirements of ANSI/ESD S20.20-2014

# 3M™ Dual Conductor Fabric Wrist Band for Monitors 2368, 2368VM

3M is a trademark of 3M Company.

### Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for one year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



### Electronics Materials Solutions Division Static Control Products

926 JR Industrial Drive  
Sanford, NC 27332-9733  
Toll-Free: 866-722-3736  
International: 919-718-0000  
Email: [3mstaticinfo@mmm.com](mailto:3mstaticinfo@mmm.com)  
[www.3mstatic.com](http://www.3mstatic.com)

Please recycle. Printed in USA.  
© 3M 2014. All rights reserved.  
78-9102-1849-0 JHA