TRIPP-LITE

USB-C Dock - 4K HDMI, USB 3.2 Gen 1, USB-A Hub, GbE, Memory Card, 100W PD Charging

MODEL NUMBER: U442-DOCK5-GY



USB-C docking station with PD Charging adds HDMI, USB-A, Ethernet and memory card ports to your Chromebook, Windows laptop or tablet.

Features

USB-C Docking Station Turns Your Device's USB-C or Thunderbolt 3 Port into a WorkstationThis USB-C dock with PD Charging expands the potential of your Windows laptop, Chromebook, smartphone or PC's USB-C or Thunderbolt 3 port. It's ideal for transmitting true 4K video and digital audio to a large display, adding a thumb drive and other USB peripherals, powering and charging a PD Charging-compliant mobile device, connecting to a Gigabit Ethernet network and a lot more—all at the same time.

Supports USB-C DisplayPort Alternate Mode for Converting Audio/Video SignalsBy connecting the built-in USB-C cable to a source device that supports USB DisplayPort Alt Mode, you can output 4K video and digital audio to an HDMI monitor, television or projector without installing special software drivers.

Transmits Crystal-Clear 4K Video and Digital Audio with True 4:4:4 ColorThe HDMI output supports 4K video resolutions up to 3840 x 2160 at 30 Hz with multi-channel sound and 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor. Connect the HDMI port to your display using an HDMI cable (sold separately). A DVI display may also be connected using an HDMI to DVI adapter (sold separately).

USB Ports Connect Keyboards, Thumb Drives and Other PeripheralsThree USB-A hub ports accept USB peripherals, such as flash drives, mice, keyboards and printers. They support 5V 2A (10W) of charging power, when connected to a PD 3.0-compliant charger, and fast USB 3.2 Gen 1 data transfer rates up to 5 Gbps (10 times faster than USB 2.0). One port provides 5V 1.5A (7.5W) of power dedicated to fast-charging your mobile device. Note: Host must support USB OTG (On-the-Go).

PD Charging Port Charges the Connected Notebook, Tablet or Other DeviceThe USB-C port supports Power Delivery (PD) 3.0 charging of connected PD Charging-compliant devices, such as laptops, Kindles, iPads and Android smartphones. Connect the device's AC wall charger to the USB-C PD port, which supports power input up to 20V 5A (100W). This port, as mentioned above, can also be used for transferring data up to 5 Gbps. PD 3.0 Fast Role Swap technology ensures all data and power connections remain stable if the wall charger becomes accidentally dislodged. Note: USB-C PD port does not support Quick Charge (QC).

Accesses a Wired Gigabit Ethernet Network The RJ45 port offers access to a Gigabit Ethernet network when Wi-Fi is unavailable or when a wired connection offers faster speeds. Connect using a UTP cable

Highlights

- Converts audio/video signals from laptops and other devices that support USB-C DisplayPort Alt Mode
- Supports 4K resolutions up to 3840 x 2160 (@ 30 Hz) for crystal-clear video
- Connect to a wired 10/100/1000 Mbps (Gigabit) Ethernet network when Wi-Fi is unavailable
- Charge the host laptop with up to 100 Watts (20V 5A) of PD Charging power output
- USB-C, USB-A and memory card ports allow connection of flash drives and other peripherals

Applications

- Play video from your laptop or PC on an HDMI display, such as an HDTV or projector
- Save data to a USB-enabled thumb drive or external hard drive
- Access a wired Gigabit Ethernet network in a location with no or spotty Wi-Fi
- Charge your notebook or laptop by connecting its wall charger to the USB-C PD Charging port
- Connect a microphone/headset to record a podcast or listen to music

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with HDMI or DVI* input

*Requires adapter (sold separately)

Package Includes

- U442-DOCK5-GY USB-C Dock, Gray
- Owner's manual



1000 Eaton Boulevard Cleveland, OH 44122 United States

(sold separately), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

Allows External Memory AccessThe memory card slots support Micro SD and SD/MMC cards for transferring data to and from your connected computer, laptop or tablet. Both slots may be used at the same time.

Built-In USB-C Cable Attaches in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for an instant connection every time.

Ready to Use Right from the Package, So You Can Plug and Play ImmediatelyThe plug-and-play USB-C dock is specifically designed for use with Windows laptops and other notebooks, smartphones, tablets and devices equipped with a USB-C or Thunderbolt 3 port. It requires no extra software to be downloaded or installed. It's about the size of a smartphone, making it easy to pack into a pocket, backpack or laptop bag for multiport convenience wherever you go.

Specifications

| OVERVIEW | |
|--------------------------------|--|
| UPC Code | 037332241016 |
| Product Type | Docking Station |
| Device Compatibility | Chromebook; Computer; Laptop; Monitor/HDTV; Phone |
| Technology | Cat5/5e; Cat6; HDMI |
| Country/Region | Global |
| Host Connector | USB C (MALE) |
| VIDEO | |
| Video Input | USB C (MALE) |
| Video Output | HDMI (FEMALE) |
| Number of Monitors Supported | 1 |
| Video Ports | HDMI (FEMALE) |
| Video Ports Details | HDMI 1.4; HDCP 1.4 |
| Resolutions Supported | 3840 x 2160 (4K x 2K) @ 30 Hz |
| Supported Resolutions | 3840x2160 (4K) |
| Max Supported Video Resolution | 3840 X 2160 (4K X 2K) @ 30HZ |
| Recommended Cabling | P568-Series High Speed 4K HDMI Cables |
| Extended Mode | Yes |
| Extended Mode Details | Extend your workspace to across a connected display at video resolutions up to 3840 x 2160 (4K x 2K) @ 30 Hz |
| Mirror Mode | Yes |
| Mirror Mode Details | Mirror video from the USB-C port on a laptop to a connected display at video resolutions up to 3840 x 2160 (4K x 2K) @ 30 Hz |
| Max Supported Color Depth | 24-bit True Color |

TRIPP-LITE

| [| 1 | | |
|--|--|--|--|
| HDR Support | Yes | | |
| 3D Video Supported | Yes | | |
| Chroma Sub Sampling | 4:2:2; 4:4:4 | | |
| EDID Support | Yes | | |
| Signal Transmission | Unidirectional | | |
| DisplayPort Alt Mode | Yes | | |
| DSC Support | Yes | | |
| DATA | | | |
| Data Ports | (3) USB A (FEMALE); (1) USB C (FEMALE) | | |
| Data Ports Details | (3) USB-A - USB 3.2 Gen 1 (5 Gbps); (1) USB-C - USB 3.2 Gen 1 (5 Gbps) | | |
| NETWORK | NETWORK | | |
| Network Ports | RJ45 (FEMALE) | | |
| STORAGE | | | |
| Card Slots | SD (FEMALE); MICRO SD (FEMALE) | | |
| Card Slots Details | SD 3.0 Memory Card slots (SD and MicroSD) can be used simultaneously | | |
| INPUT | | | |
| Bus Powered | Yes | | |
| BATTERY | | | |
| Battery Charging (5V/1.5A Port) | Yes | | |
| POWER | | | |
| USB Power Delivery (PD) Charging Support | Yes | | |
| USB Power Delivery (PD) Charging Specification | 3.0 | | |
| USER INTERFACE, ALERTS & CON | TROLS | | |
| LED Indicators | White (Connection to Power) and Orange (Activity) | | |
| CHARGING | | | |
| Number of Charging Ports | 4 | | |
| Total Charging Amps | 2 | | |
| Total Charging Watts | 100 | | |
| Charging Port Type | (3) USB A (FEMALE); USB C (FEMALE) | | |
| | | | |



| Charging Ports | USB-C: 100W (20V 5A) Power Delivery (PD 3.0); USB-A: 5V 1.5A (7.5W) |
|---------------------------------------|--|
| Charging Ports Details | One USB-A port supports 5V 1.5A (7.5W) for quickly charging mobile devicesAll three USB-A ports share 5V 2A (10W) when connected to a PD 3.0 compliant chargerThe USB-C PD Charging/Data port provides up to 20V 5A (100W) to charge the host laptop via a compatible wall charger |
| Charging Ports / Amps | 1.5A; 5A |
| Compatible Devices | Chromebook; Laptop; Smartphone; Tablet |
| PHYSICAL | |
| Color | Black |
| Material of Construction | Aluminum |
| Connector Color | Gray |
| Cable Jacket Rating | VW-1 |
| Cable Outer Diameter (OD) | 4.2mm |
| Cable Length (ft.) | 0.39 |
| Cable Length (m) | 0.12 |
| Cable Length (in.) | 4.72 |
| Cable Length (cm) | 12 |
| Total Number of Ports | 8 |
| Shipping Dimensions (hwd / in.) | 0.91 x 5.51 x 3.94 |
| Shipping Dimensions (hwd / cm) | 2.31 x 14.00 x 10.01 |
| Shipping Weight (lbs.) | 0.25 |
| Shipping Weight (kg) | 0.11 |
| Unit Dimensions (hwd / in.) | 0.500 x 4.100 x 1.900 |
| Unit Dimensions (hwd / cm) | 1.3 x 10.5 x 4.9 |
| Unit Packaging Type | Box |
| Unit Weight (Ibs.) | 0.25 |
| Unit Weight (kg) | 0.11 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32° to 113°F (0° to 45°C) |
| Storage Temperature Range | 14° to 158°F (-10° to 70°C) |
| Operating Humidity Range | 10% to 85% RH, Non-Condensing |
| Storage Humidity Range | 5% to 90% RH, Non-Condensing |
| Power Provided to Connected Device(s) | USB-A: 5V/2A (10W), USB-C PD: 20V/5W (100W) |
| COMMUNICATIONS | |
| Network Compatibility | 1 Gbps (Gigabit) |

TRIPP-LITE

| EDID Compatible | Yes | | |
|----------------------------|---|--|--|
| IEEE Standards Supported | 802.3; 802.3az; 802.3u; 802.3x | | |
| CONNECTIONS | CONNECTIONS | | |
| Number of Ports | 8 | | |
| Ports | 1 | | |
| Ports Detail | Connect to a wired Gigabit Ethernet network via the built-in RJ45 port on the dock. | | |
| Dock Connectors | USB-C PD Data/Charging, (3) USB-A 3.2 Gen 1, MICRO SD, SD, HDMI, RJ45 | | |
| Side A - Connector 1 | USB C (MALE) | | |
| Side B - Connector 1 | HDMI (FEMALE) | | |
| Side B - Connector 2 | RJ45 (FEMALE) | | |
| Side B - Connector 3 | (3) USB A (FEMALE) | | |
| Side B - Connector 4 | USB C (FEMALE) | | |
| Side B - Connector 5 | MICRO SD (FEMALE) | | |
| Side B - Connector 6 | SD (FEMALE) | | |
| Connector Plating | Nickel | | |
| Connector Style | Straight | | |
| FEATURES & SPECIFICATIONS | | | |
| USB Hub Ports | Yes | | |
| Number of USB Hub Ports | 3 | | |
| USB Specification | USB 3.2 Gen 1 (up to 5 Gbps) | | |
| Data Transfer Rate | 5 Gbps | | |
| MST Support | No | | |
| Multi-Resolution Support | No | | |
| Network Speed Support | 10 Mbps; 100 Mbps (Fast Ethernet); 1 Gbps (Gigabit) | | |
| Ethernet Support | Yes | | |
| UASP Support | No | | |
| Auto MDIX Support | Yes | | |
| Full Duplex Support | Yes | | |
| Suspend Mode Support | Yes | | |
| Remote Wakeup Support | Yes | | |
| SD Card Specification | SD; Micro SD | | |
| HDCP Specification | 1.4 | | |
| Driver Required | No | | |
| Recommended Category Cable | Cat5/Cat5e/Cat6 Cables | | |



| STANDARDS & COMPLIANCE | | |
|--|---|--|
| Product Certifications | ICES (Canada); NOM (Mexico) | |
| Product Compliance | CE (Europe); FCC (USA); REACH; RoHS; UKCA | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | 3-year limited warranty | |



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.