


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR SHOWN WITHOUT WRITTEN PERMISSION.

Item No.	Part No.	Description	IPI CHECK	EOR CHECK	APPLICABLE HOUSINGS		
1	SSUH-003T-P0.15	SUH Connector Contact			NO. OF CIRCUITS	HOUSING PART NO. WITH PROTRUSIONS	HOUSING PART NO. WITHOUT PROTRUSIONS
2	UL1571 (0.58 OD), 28 AWG	White			2	SUHR-02V-S-B	SUHR-02V-S

Electrical Specifications
Current: 1.0AAC/DC
Voltage: 30V AC/DC

3	SUHR-03V-S-B	SUHR-03V-S
4	SUHR-04V-S-B	SUHR-04V-S
5	SUHR-05V-S-B	SUHR-05V-S
6	SUHR-06V-S-B	SUHR-06V-S
10	SUHR-10V-S-B	SUHR-10V-S
12	SUHR-12V-S-B	SUHR-12V-S
14	SUHR-14V-S-B	SUHR-14V-S
16	SUHR-16V-S-B	SUHR-16V-S
20	SUHR-20V-S-B	SUHR-20V-S



All dimensions are in millimeters with a default tolerance of +/- 5.0 unless otherwise specified.	CUSTOMER NAME			
	DESCRIPTION 0.8mm Pitch SUH Series Standard Leads - 4" Inside Length DOUBLE END LEADS			
Drawn By: Larissa Mosley	SIZE	CUSTOMER PART NO.	PART NO.	REV
Checked By: Steven Pilkington	SCALE 1:1	DRAWING NO. GAM-301	ASSUHSSUH28W102	DATE 4/18/2018

ZONE	REV	DESCRIPTION	DATE	APPROVED
	1	Add Electrical Specifications	6/29/2018	LM