

SPECIFICATION CONTROL DRAWING			2022Y1422
CHEMINAX	120 OHM, AWG 22, 19 STRANDS OF AWG 34, OPTIMIZED SHIELD, TWINAXIAL CABLE	Date	7-18-13
		Revision	B
THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.			
CONSTRUCTION DETAILS		ELECTRICAL CHARACTERISTICS	
DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE DESIGNATED. CONDUCTORS AWG 22, 19 Strands of AWG 34, Silver-Coated Copper DIELECTRICS Rayfoam H Colors - White/Light Blue FILLERS Radiation-Crosslinked Modified ETFE SHIELD AWG 38, Silver-Coated Copper Optimized JACKET Modified FEP		CHARACTERISTIC IMPEDANCE 120 ± 12 ohms, Method D at 1 MHz MUTUAL CAPACITANCE 12.7 pF/ft. (nominal) VELOCITY OF PROPAGATION 77% (nominal) SURFACE TRANSFER IMPEDANCE 225 milliohms/meter (maximum) at 0.1 to 1 MHz (Per MIL-DTL-85485)	
		ADDITIONAL REQUIREMENTS	
		ELECTRICAL	
		CONDUCTOR RESISTANCE (prior to cabling) 14.9 ohms/1000 ft. (nominal) INSULATION RESISTANCE 10,000 megohms (minimum) for 1000 ft. JACKET FLAWS SPARK TEST 1.0 kV (rms) IMPULSE TEST 6.0 kV (peak) VOLTAGE WITHSTAND (DIELECTRIC) 1000 volts (rms) (minimum)	
		ENVIRONMENTAL	
		FLAMMABILITY Method B HEAT SHOCK 225°C LOW TEMPERATURE-COLD BEND -55°C/5.50 inch mandrel VOLTAGE WITHSTAND (Post Environmental) 1000 volts (rms), 1 minute	
		PHYSICAL	
		INSULATION (DIELECTRIC) (prior to cabling) ELONGATION 50% (minimum) TENSILE STRENGTH 600 lbf/in ² (minimum) JACKET ELONGATION 200% (minimum) TENSILE STRENGTH 2000 lbf/in ² (minimum) JACKET THICKNESS .010 inch (nominal) SHIELD COVERAGE 90% (minimum)	
		ENGINEERING REFERENCE	
		TEMPERATURE REATING -65°C to +200°C WEIGHT 25.7 lbs/1000 ft. (nominal)	
Outer jacket color will be translucent white (designated by a "-9X" appended to the part number, e.g. 2022Y1422-9X) unless otherwise specified.			
Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.			
Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.			
Page 1 of 1	Rayfoam, Cheminax, Raychem, TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.		



Raychem Wire & Cable
 501 Oakside Avenue
 Redwood City, California 94063-3800
 1-800-227-8816 Fax: 1-650-361-6297

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.