

3A, 40V - 200V Schottky Barrier Surface Mount Rectifier

FEATURES

- AEC-Q101 qualified
- Low power loss, high efficiency
- Ideal for automated placement
- High surge current capability
- Moisture sensitivity level: level 1, per J-STD-020
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21

APPLICATIONS

- Switching mode power supply (SMPS)
- Adapters
- Lighting application
- On-board DC/DC converter

MECHANICAL DATA

- Case: SOD-128
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 2 whisker test
- Polarity: Indicated by cathode band
- Weight: 0.028g (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
I_F	3	A
V_{RRM}	40 - 200	V
I_{FSM}	70	A
T_{JMAX}	150	°C
Package	SOD-128	
Configuration	Single die	


SOD-128


ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)							
PARAMETER	SYMBOL	SS34 FSH	SS36 FSH	SS310 FSH	SS315 FSH	SS320 FSH	UNIT
Marking code on the device		34FSH	36FSH	310FSH	315FSH	320FSH	
Repetitive peak reverse voltage	V_{RRM}	40	60	100	150	200	V
Reverse voltage, total rms value	$V_{R(RMS)}$	28	42	70	105	140	V
Forward current	I_F	3					A
Surge peak forward current, single half sine-wave superimposed on rated load	$t = 8.3\text{ms}$	70					A
	$t = 1.0\text{ms}$	170					A
Junction temperature	T_J	-55 to +150					°C
Storage temperature	T_{STG}	-55 to +150					°C

THERMAL PERFORMANCE			
PARAMETER	SYMBOL	TYP	UNIT
Junction-to-lead thermal resistance	$R_{\theta JL}$	16	°C/W
Junction-to-ambient thermal resistance	$R_{\theta JA}$	71	°C/W
Junction-to-case thermal resistance	$R_{\theta JC}$	14	°C/W

Thermal Performance Note: Units mounted on PCB (5mm x 5mm Cu pad test board)

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)						
PARAMETER		CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage ⁽¹⁾	SS34FSH	$I_F = 1.5\text{A}, T_J = 25^\circ\text{C}$	V_F	0.41	-	V
		$I_F = 3.0\text{A}, T_J = 25^\circ\text{C}$		0.47	0.59	V
		$I_F = 1.5\text{A}, T_J = 125^\circ\text{C}$		0.31	-	V
		$I_F = 3.0\text{A}, T_J = 125^\circ\text{C}$		0.41	0.53	V
	SS36FSH	$I_F = 1.5\text{A}, T_J = 25^\circ\text{C}$		0.51	-	V
		$I_F = 3.0\text{A}, T_J = 25^\circ\text{C}$		0.62	0.72	V
		$I_F = 1.5\text{A}, T_J = 125^\circ\text{C}$		0.45	-	V
		$I_F = 3.0\text{A}, T_J = 125^\circ\text{C}$		0.55	0.63	V
	SS310FSH	$I_F = 1.5\text{A}, T_J = 25^\circ\text{C}$		0.70	-	V
		$I_F = 3.0\text{A}, T_J = 25^\circ\text{C}$		0.76	0.88	V
		$I_F = 1.5\text{A}, T_J = 125^\circ\text{C}$		0.57	-	V
		$I_F = 3.0\text{A}, T_J = 125^\circ\text{C}$		0.63	0.77	V
	SS315FSH	$I_F = 1.5\text{A}, T_J = 25^\circ\text{C}$		0.76	-	V
		$I_F = 3.0\text{A}, T_J = 25^\circ\text{C}$		0.82	0.95	V
		$I_F = 1.5\text{A}, T_J = 125^\circ\text{C}$		0.62	-	V
		$I_F = 3.0\text{A}, T_J = 125^\circ\text{C}$		0.68	0.80	V
	SS320FSH	$I_F = 1.5\text{A}, T_J = 25^\circ\text{C}$		0.79	-	V
		$I_F = 3.0\text{A}, T_J = 25^\circ\text{C}$		0.85	0.95	V
		$I_F = 1.5\text{A}, T_J = 125^\circ\text{C}$		0.64	-	V
		$I_F = 3.0\text{A}, T_J = 125^\circ\text{C}$		0.71	0.80	V
Reverse current @ rated V_R ⁽²⁾	SS34FSH SS36FSH	$T_J = 25^\circ\text{C}$	I_R	-	200	μA
		$T_J = 125^\circ\text{C}$		-	80	mA
	SS310FSH SS315FSH SS320FSH	$T_J = 25^\circ\text{C}$		-	10	μA
		$T_J = 125^\circ\text{C}$		-	1	mA
Junction capacitance	SS34FSH	1MHz, $V_R = 4.0\text{V}$	C_J	172	-	pF
	SS36FSH			133	-	pF
	SS310FSH			86	-	pF
	SS315FSH			69	-	pF
	SS320FSH			54	-	pF

Notes:

1. Pulse test with $PW = 0.3\text{ms}$
2. Pulse test with $PW = 30\text{ms}$

ORDERING INFORMATION		
ORDERING CODE⁽¹⁾	PACKAGE	PACKING
SS3xFSH	SOD-128	14,000 / Tape & Reel

Notes:

1. "x" defines voltage from 40V(SS34FSH) to 200V(SS320FSH)

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics




Fig.5 Typical Reverse Characteristics





Fig.6 Typical Forward Characteristics



CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.7 Typical Reverse Characteristics




Fig.9 Typical Reverse Characteristics




Fig.11 Typical Reverse Characteristics




Fig.8 Typical Forward Characteristics




Fig.10 Typical Forward Characteristics






Fig.12 Typical Forward Characteristics



CHARACTERISTICS CURVES


($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.13 Typical Transient Thermal Impedance




PACKAGE OUTLINE DIMENSIONS

SOD-128



DIM.	Unit (mm)		Unit (inch)	
	Min.	Max.	Min.	Max.
A	0.90	1.10	0.035	0.043
A1	0.00	0.10	0.000	0.004
b	1.60	1.90	0.063	0.075
c	0.10	0.22	0.004	0.009
D	2.30	2.70	0.091	0.106
E	4.40	5.00	0.173	0.197
E1	3.60	4.00	0.142	0.157
L	0.40	0.80	0.016	0.031
L1	0.30	0.60	0.012	0.024

SUGGESTED PAD LAYOUT



Symbol	Unit (mm)	Unit (inch)
A	2.10	0.083
B	1.40	0.055
C	4.40	0.173
D	3.00	0.118
E	5.80	0.228

MARKING DIAGRAM



- P/N = Marking Code
- YW = Date Code
- F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.