




UNIT: mm



CABLE WHITE PRINT
 HI-SPEED USB Revision 2.0 SHIELDED 28AWG/1P+24AWG/2C
 E189529 AWM STYLE 2725 80C 30V VW-1 VEGA TECH

PIN ASSIGNMENT:



Electrical test:
 1. 100% short, open, miswire test
 2. Conduct resistance: 2 Ohm(max)
 3. Insulation resistance: 5Mohm(min)
 4. dielectric test: DC 300V

⑨	PE BAG	L/10	CLEAR SIZE: 280*330*40.05mm PRINT BLACK"MADE IN CHINA"+10PCS"
⑧	PE BAG	1	CLEAR SIZE: 130*230*40.05mm PRINT BLACK"MADE IN CHINA"+1PCS"
⑦	TIE	1	WHITE L=100mm
⑥	IN JACKET	3g	CLEAR LDPE (MOULD NO: NM-027)
⑤	OUT JACKET	7g	BLACK PVC-40P (MOULD NO: NM-83)
④	OUT JACKET	6g	BLACK PVC-40P (MOULD NO: NM-40)
③	CABLE	1	BLACK USB2.0 UI2725 28#/1P+24#/2C+A+B3 OD: 4.7mm L=1780 ± 10mm
②	CONN	1	USB2.0 A FEMALE SHELL: NICKEL PIN G/F SHORT TYPE INSULATOR COLOR: WHITE
①	CONN	1set	USB2.0 A MALE SHELL: NICKEL PIN G/F 3PCS-TYPE INSULATOR COLOR: WHITE
NO.	NAME	QTY	SPECIFICATION

CNC Tech, LLC
 Industrial Cable and Connector Technology

DRAWN	Andy	DRAWING NO	VG/LJQ-094-020
CHECKED		CUSTOMER	CNC
APPROVAL		ITEM NO.	102-1010-B1-00180
DECIDED		DATE	2013-8-23
VERSIONS/EDITION	A/0	PROJECTION	

A

B

C

D

A

B

C

D

4

3

2

1