

## Cable gland - G-INS-PG48-L68N-NNES-S - 1411181

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 34 mm ... 44 mm, Shielding: No, Connecting thread: Pg48, Color: silver



### Key Commercial Data

Packing unit	1 pc
Custom tariff number	74199990
Country of origin	Turkey

### Technical data

#### Dimensions

Length	63 mm
Wrench size, union nut	64 mm
Wrench size, support	64 mm
Hexagon angular dimension GRP	70 mm
Length of the connecting thread	14 mm
Feed-through hole diameter	59.4 mm ... 59.8 mm
External cable diameter	34 mm ... 44 mm

#### Ambient conditions

Degree of protection	IP68 (5 bar, 30 min.)
Ambient temperature (operation)	-20 °C ... 100 °C (static)

#### General

No. of conductors	1
Cable gland material	Brass, nickel-plated
Seal material	Neoprene
Cable seal material	Neoprene
O-ring material	NBR

# Cable gland - G-INS-PG48-L68N-NNES-S - 1411181

## Technical data

### General

Shielded	No
Thread type on connection side	Pg48
Torque	40 Nm ... 50 Nm (Union nut)
Color	silver

## Classifications

### eCl@ss

eCl@ss 5.1	27081002
eCl@ss 6.0	27081002
eCl@ss 8.0	27149109

### ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

## Approvals

### Approvals

---

Approvals

UL Listed

---


Ex Approvals

---

Approvals submitted

---


### Approval details

UL Listed 
---

## Drawings

## Cable gland - G-INS-PG48-L68N-NNES-S - 1411181

Dimensional drawing



Dimensional drawing

---

Phoenix Contact 2016 © - all rights reserved  
<http://www.phoenixcontact.com>