

HT-1006 50 Ohm ATTENUATOR SPECIFICATIONS

**HT-1006 10dB
6GHz / 2w**



■ ELECTRICAL SPECIFICATIONS

ITEM	MIN	TYP	MAX	UNIT
Frequency Range	DC ~ 6000			MHz
Impedance	50			Ω
Insertion Loss (0.3 ~ 3000 MHz)	9.7	10	10.3	dB
Return Loss / VSWR (0.3 ~ 3000 MHz)	25 / 1.119	30 / 1.065		dB
Flatness (0.3 ~ 3000 MHz)		0.3	0.6	dB
Insertion Loss (3001 ~ 6000 MHz)	9.5	10	10.5	dB
Return Loss / VSWR (3001 ~ 6000 MHz)	20 / 1.222	25 / 1.119		dB
Flatness (3001 ~ 6000 MHz)		0.5	1	dB
Power Rating		1.0	2.0	W

■ MECHANICAL SPECIFICATIONS

ITEM	DESCRIPTION	UNIT
Housing	Copper Tube	
Connector	50 Ω , Male & Female SMA	
Connector Screw Thread	W 1/4"-36UNF	inch
Dimensions	9.35(ϕ) x 30	mm
Net Weight	8	g

HT-1006

Insertion Loss and Return Loss

Span: 6000MHz




Fig.1