



Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch lever
Device short name	ZCY
Product Compatibility	XCKT XCMD XCKP XCKD
Associated head	ZCE09
Movement of operating head	Rotary
Type of operator	Stay put forked arm with rollers stay put 2 tracks)
Tracks	21/35 mm XCMD 25/39 mm XCKD 25/39 mm XCKP 25/39 mm XCKT
Type of approach	Lateral approach

Complementary

Switch actuation	By specific cam
Positive opening	Without

Environment

Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22413-LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	T
GTIN	3389110192049
Nbr. of units in pkg.	1
Package weight(Lbs)	0.81 oz (23.0 g)
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.59 in (1.5 cm)
Package 1 width	2.36 in (6 cm)
Package 1 Length	1.85 in (4.7 cm)
Unit Type of Package 2	BAG
Number of Units in Package 2	10
Package 2 Weight	8.29 oz (235.0 g)
Package 2 Height	1.57 in (4 cm)
Package 2 width	3.94 in (10 cm)
Package 2 Length	3.94 in (10 cm)

Unit Type of Package 3	S01
Number of Units in Package 3	200
Package 3 Weight	10.94 lb(US) (4.962 kg)
Package 3 Height	5.91 in (15 cm)
Package 3 width	5.91 in (15 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------