



NOTES:

- SWITCH SPECIFICATIONS:**
TOGGLE SWITCH, UL RECOGNIZED
CIRCUIT: DPDT
CIRCUIT FUNCTION: ON-NONE-ON
RATING: 6A @ 125 VAC per UL1054
3A @ 250 VAC PER UL1054
CONTACT RESISTANCE: 20mΩ MAX.
INSULATION RESISTANCE: DC 500V 100MΩ MIN.
DIELECTRIC WITHSTANDING VOLTAGE: AC 1500V 1 MINUTE.
OPERATING TEMPERATURE: -20°C TO 65°C.
ELECTRICAL LIFE: 6,000 MAKE AND BREAK CYCLES AT FULL LOAD PER UL1054.
TERMINAL STYLE: SOLDER TERMINALS, SILVER PLATED
- MATERIALS:**
FLANGE - ZINC
SWITCH ACTUATOR HARDWARE - COPPER ALLOY, NICKEL PLATED.
SWITCH INSULATOR - THERMOPLASTIC
SWITCH TERMINALS & CONTACTS - COPPER ALLOY, AND/OR COPPER ALLOY SILVER PLATED
- FOR FLANGE MOUNTING SCREWS TO BE SHIPPED WITH ASSEMBLY, ADD THE SUFFIX "PKG" TO THE PART NUMBER.
- THESE PRODUCTS ARE RoHS COMPLIANT.

PART NUMBER	FLANGE FINISH
EHTSL	NICKEL
EHTSLB	BLACK

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					UNLESS OTHERWISE SPECIFIED			FINISH	
					1. ALL DIMENSIONS IN INCHES			MATERIAL	
					- TWO PLACE DECIMALS ±0.02			SPEC No.	
					- THREE PLACE DECIMALS ±0.005			FIRST USED ON	
								SCALE	
								2:1	
					DATE DRAWN	BY	CHKD	APVD	Switchcraft [®]
					07/28/09	BS	PNK	SRC	
								SHEET 1 OF 1	
								PART No.	
								EHTSL SERIES	
								REV	
								A	

REV	ECO NUMBER	DATE	BY	APVD
A	26781	6-9-11	TO	TJK
REVISIONS				

DO NOT SCALE DRAWING