

**Ratings**

Voltage: 150 V  
 Temperature: -40~70 °C

**Conductor**

Conductor count: 4  
 Gauge: 26 AWG AWG 0.13 mm<sup>2</sup>  
 Material: Tinned copper strands  
 Strand size:  $\phi 0.08 \times 26$   
 Resistance at 20 °C: 150  $\Omega$  /km max

**Insulator**

Material: HDPE  
 Color: white, black, red, yellow  
 Diameter:  $\phi 0.9 \pm 0.10$  mm  
 Nominal thickness: 0.20 mm  
 Resistance at 20 °C: 100 M $\Omega$  /km min

**Wrap**

Material: cotton paper

**Filler**



Material: aramid fiber

**Outer jacket**

Material: TPU  
 Color: gray  
 Diameter:  $\phi 3.4 \pm 0.20$  mm  
 Nominal thickness: 0.50 mm

**Tests**

Tensile strength: 26 kgf min  
 Dielectric test: 1500 V dc for 1 minute without breakdown  
 Bend test at 200 g,  $\pm 60^\circ$ , 30 cycles /min: 15,000 cycle minimum



Revision:	Date:	Description:
A	8/23/2022	Initial release

Prepared: **PB**  
Digitally signed by PB  
 Date: 2022.09.20  
 10:43:13 -07'00'

Verified: **MP**  
Digitally signed by MP  
 Date: 2022.09.21  
 10:15:09 -07'00'

Dimensions are in millimeters.  
 Tolerances:  
 X:  $\pm 0.5$  mm  
 X.X:  $\pm 0.3$  mm  
 X.XX:  $\pm 0.05$  mm

Notes:

RoHS compliant  
 Jacket meets ISO 10993 Biological Compatibility  
 Phthalate and halogen free  
 Function test: no open, no short, no intermittent

Description:  
 Wire, 4C TS, 26 AWG, 150V, 70C, 3.4 mm, TPU, 75A, gray, WBL

**TENSILITY**

tel 1.541.323.3228 800 877.670.7118  
 fax 1.541.323.4202 web tensility.com

Size: A Part number: 30-02722

Scale: 16:1 Sheet 1 of 1