

## Features

- Fast Switching
- Improved dv/dt Capability
- Excellent Package for Good Heat Dissipation
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

## Maximum Ratings

- Operating Junction Temperature Range : -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance:1.5°C/W Junction to Case

Parameter	Symbol	Rating	Unit	
Drain-Source Voltage	$V_{DS}$	200	V	
Gate-Source Voltage	$V_{GS}$	±30	V	
Continuous Drain Current	$I_D$	$T_C=25^\circ\text{C}$	9	A
		$T_C=100^\circ\text{C}$	5.83	A
Pulsed Drain Current <sup>(Note 1)</sup>	$I_{DM}$	36	A	
Single Pulse Avalanche Energy <sup>(Note 2)</sup>	$E_{AS}$	320	mJ	
Peak Diode Recovery Energy <sup>(Note 3)</sup>	dV/dt	5	V/ns	
Total Power Dissipation	$P_D$	83	W	



Note:

1.Pulse Width Limited by Maximum Junction Temperature.

2.L=10mH,  $I_{AS}=8\text{A}$ ,  $V_{DD}=50\text{V}$ ,  $R_G=25\Omega$ , Starting  $T_J=25^\circ\text{C}$

3. $I_{SD}\leq 9\text{A}$ ,  $di/dt\leq 200\text{A}/\mu\text{s}$ ,  $V_{DD}\leq BV_{DSS}$ , Starting  $T_J=25^\circ\text{C}$ .


## Internal Structure and Marking Code



YWWTT: 5 codes in total  
Y is the year  
WW is the cycle  
TT is the line type

# N-CHANNEL MOSFET

## DPAK(TO-252)



DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	0.087	0.094	2.20	2.40	
B	0.000	0.005	0.00	0.13	
C	0.026	0.034	0.66	0.86	
D	0.018	0.023	0.46	0.58	
E	0.256	0.264	6.50	6.70	
F	0.201	0.215	5.10	5.46	
G	0.190		4.83		TYP.
H	0.236	0.244	6.00	6.20	
I	0.086	0.094	2.18	2.39	
J	0.386	0.409	9.80	10.40	
K	0.114		2.90		TYP.
L	0.055	0.067	1.40	1.70	
M	0.063		1.60		TYP.
O	0.043	0.051	1.10	1.30	
Q	0.000	0.012	0.00	0.30	
V	0.211		5.35		TYP.

**Electrical Characteristics @ 25°C (Unless Otherwise Specified)**

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
<b>Static Characteristics</b>						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	200			V
Breakdown Voltage Temperature Coefficient	$\frac{\Delta V_{(BR)DSS}}{\Delta T_J}$	Reference to 25°C, $I_D=250\mu A$		0.25		V/°C
Gate-Source Leakage Current	$I_{GSS}$	$V_{DS}=0V, V_{GS}=\pm 30V$			±100	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=200V, V_{GS}=0V$			1	μA
		$V_{DS}=160V, V_{GS}=0V, T_C=125^\circ C$			10	
Gate-Threshold Voltage <sup>(Note 4)</sup>	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1	1.9	3	V
Drain-Source On-Resistance <sup>(Note 4)</sup>	$R_{DS(on)}$	$V_{GS}=10V, I_D=4.5A$		0.21	0.25	Ω
Forward Transconductance <sup>(Note 4)</sup>	$g_{FS}$	$V_{DS}=30V, I_D=4.5A$		9.2		S
<b>Dynamic Characteristics<sup>(Note 5)</sup></b>						
Input Capacitance	$C_{iss}$	$V_{DS}=25V, V_{GS}=0V, f=1MHz$		509		pF
Output Capacitance	$C_{oss}$			51.5		
Reverse Transfer Capacitance	$C_{rss}$			3.2		
Total Gate Charge	$Q_g$	$V_{DD}=160V, V_{GS}=10V, I_D=9A$		11.8		nC
Gate-Source Charge	$Q_{gs}$			2.36		
Gate-Drain Charge	$Q_{gd}$			3.98		
Turn-On Delay Time	$t_{d(on)}$	$V_{DD}=100V, I_D=9A, R_G=10\Omega, V_{GS}=10V$		10.33		ns
Turn-On Rise Time	$t_r$			10.7		
Turn-Off Delay Time	$t_{d(off)}$			29.1		
Turn-Off Fall Time	$t_f$			11.1		
<b>Drain-Source Body Diode Characteristics</b>						
Continuous Body Diode Current	$I_S$	$T_C=25^\circ C$			9	A
Pulsed Diode Forward Current	$I_{SM}$				36	
Body Diode Voltage	$V_{SD}$	$I_S=9A, V_{GS}=0V$			1.4	V
Reverse Recovery Time	$t_{rr}$	$V_{GS}=0V, I_F=9A, di/dt=100A/\mu s$		201		ns
Reverse Recovery Charge	$Q_{rr}$				663	

Note 4. Pulse Test : Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.

5. Guaranteed by Design, Not Subject to Production Testing.

**Curve Characteristics**

Fig. 1 - Output Characteristics




Fig. 2 - Transfer Characteristics




Fig. 3 -  $R_{DS(ON)} - I_D$




Fig. 4 -  $I_S - V_{SD}$




Fig. 5 - Capacitance Characteristics





Fig. 6 - Gate Charge



## Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 2.5Kpcs/Reel

Note : Adding "-HF" Suffix for Halogen Free, eg. Part Number-TP-HF

### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp** . and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.