

Han 10EMC/B-HTE-HC-for SL-M40-HMC



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 19 62 210 0448 |
| Specification | Han 10EMC/B-HTE-HC-for SL-M40-HMC |
| HARTING eCatalogue | https://b2b.harting.com/19622100448 |

Identification

| | |
|--------------------------|------------------------|
| Category | Hoods/Housings |
| Series of hoods/housings | Han [®] EMC/B |
| Type of hood/housing | Hood |
| Type | High construction |

Version

| | |
|----------------------|---|
| Size | 10 B |
| Version | Top entry |
| Cable entry | 1x M40 |
| Locking type | Single locking lever |
| Field of application | Hoods/Housings for higher EMC requirements Special hoods and housings for high mating cycles |

Technical characteristics

| | |
|---|--|
| Limiting temperature | -40 ... +125 °C |
| Note on the limiting temperature | For use as a connector according to IEC 61984. |
| Mating cycles with other HMC components | ≥10,000 |
| Degree of protection acc. to IEC 60529 | IP65 IP66 |
| Type rating acc. to UL 50 / UL 50E | 4 12 |

Material properties

| | |
|-------------------------|--------------------|
| Material (hood/housing) | Aluminium die-cast |
|-------------------------|--------------------|



Pushing Performance
Since 1945

Material properties

| | |
|------------------------|-----------|
| Surface (hood/housing) | Uncoated |
| Colour (hood/housing) | Unpainted |

Specifications and approvals

| | |
|-----------|--|
| UL / CSA | UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE | Yes |
| Approvals | DNV GL |

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 1 |
| Net weight | 150 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| GTIN | 5713140171817 |
| eCl@ss | 27440202 Shell for industrial connectors |