

- > for cutting copper and aluminum cables, single and multi-stranded wire
- > not suitable for steel wire and hard drawn copper conductors
- > precision ground, hardened blades
- > clean and smooth cut without crushing and deformation
- > easy cutting with one-hand operation
- > pinch guard prevents operators' fingers being pinched
- > adjustable bolted joint, self-locking
- > high-grade special tool steel; forged, oil-hardened

### Style 2

Internal opening spring, protected and captive

### Style 4

Multifunctional tool for working on NYM cable from 3 x 1.5 mm<sup>2</sup> to 5 x 2.5 mm<sup>2</sup> (cutting, stripping insulation); universal stripping area for both solid conductor cross-sections; reliable alignment of the cable in the stripping area due to V-shaped blade geometry

### 95 12 165 T BKA\*

Pliers with integrated tether attachment point for tool drop protection system



Cut performed with a Diagonal Cutter: high effort required, inaccurate cut, considerable deforming and crushing of the cable



Cut performed with a Cable Shear: easy, clean cut without any deformation of the cable



The locking device keeps shears with spring inside the joint closed



95 11 165  
⊕ ⊖



95 12 165  
⊕ ⊖



95 12 165 T BKA  
⊕ ⊖



95 18 165 US  
⚠ 1000 V ASTM ⊕



95 21 165  
⊕ ⊖



95 41 165  
⊕ ⊖

Product Number	Packaging	↔ Inch mm	⊕ ⊖	Tool	Handles	Style	Cutting capacities			⚖ lbs
							∅ Inch ∅ mm	⊕ mm <sup>2</sup>	AWG	
95 11 165	X	6 1/2 165	⊕ ⊖	burnished	plastic coated	1	19/32 15	50	1/0	0.49
95 12 165	X	6 1/2 165	⊕ ⊖	burnished	multi-component grips	1	19/32 15	50	1/0	0.55
95 12 165 T BKA	X	6 1/2 165	⊕ ⊖	burnished	multi-component grips, integrated tether attachment point	1	19/32 15	50	1/0	0.56
95 18 165 US	X	6 1/2 165	⚠ 1000 V ASTM ⊕	burnished	insulated, multi-component grips, ASTM-tested	1	19/32 15	50	1/0	0.58
95 21 165	X	6 1/2 165	⊕ ⊖	burnished	plastic coated	2	19/32 15	50	1/0	0.50
95 22 165		6 1/2 165	⊕ ⊖	burnished	multi-component grips	2	19/32 15	50	1/0	0.56
95 41 165		6 1/2 165	⊕ ⊖	burnished	plastic coated	4	15/32 12	35	1/0	0.49

\*Learn more about our tethered tool system on pages 207-211