



Note :

1. Glue apply across the soldered point.

PIN ASSIGNMENT :

P1	P2	P3
5 Yellow(GND)	5	5
4 Brown(IO)	4	-
3 Black(D+)	-	3
2 White(D-)	-	2
1 Red(VBUS)	1	-

TE P/N: 0-2009025-1
 CUSTOMER P/N: SMS05001004

AR	KG	POLYAMIDE ADHESIVE	10
2	PC	RECEPTACLE MINI USB CONNECTOR	9
1	PC	SINGLE LAYER PCB 11.96X45mm	8
AR	MR	HEAT SHRINK TUBING, OD=6.0mm, COLOR: BLACK	7
AR	MR	HEAT SHRINK TUBING, OD=1.0mm, COLOR: BLACK	6
AR	KG	INNER MOLD PE.	5
AR	MR	UL TAPE,W:9MM, Color: BLACK	4
AR	KG	OVERMOLD,PVC:90±3, COLOR: BLACK(BK01)	3
AR	MR	CABLE, UL2725,1P*28AWG+3C*28AWG, UN SHIELD CO	2
1	PC	COLOR:BLACK(BK01).OD=4.1±0.2MM	1
-1	U/M	MINI USB B PLUG,5P,SOLDER TYPE,CONTACT:GOLD FLASH	1
		SHELL:NICKEL PLATED,INSULATION:BLACK	
		DESCRIPTION	ITEM

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	0 PLC ±-
	1 PLC ±-
	2 PLC ±-
	3 PLC ±-
	4 PLC ±-
	FINISH ±-
MATERIAL	

DMN	19Aug2008	Tyco Electronics	Tyco Electronics Corporation
CHK	19Aug2008		VAO Asia Pacific
APVD	19Aug2008		
NAME			
SIZE			
CAGE CODE			
DRAWING NO			
RESTRICTED TO			

HOOK USB Assembly

SCALE: - SHEET: 1 of 1 REV: A