

# Product data sheet

Specifications



## ClimaSys forced vent. IP54, 300m<sup>3</sup>/h, 115V, with outlet grille and filter G2

NSYCVF300M115PF

### Overview

Lead time Usually Ships within 4 Weeks

### Main

Range	ClimaSys
Product name	ClimaSys CV
Product or component type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 300 m <sup>3</sup> /h at 50 Hz Free flow rate with standard filter: 350 m <sup>3</sup> /h at 60 Hz
[Us] rated supply voltage	75...126 V
Input voltage	115 V 50/60 Hz

### Complementary

Absorbed power	36 W 50 Hz 36 W 60 Hz
[In] rated current	0.35 A 50 Hz 0.32 A 60 Hz
Noise level < at	55...56 dB
Bearing type	Ball
Height	268 mm external:
Width	248 mm external:
Depth	116 mm external:
Cut-out dimensions	223 x 223 mm
Product weight	1.3 kg
Material	Outlet grille: injected thermoplastic (ASA PC)
Colour	Outlet grille: grey (RAL 7035)
Ambient air temperature for operation	-10...70 °C
Ambient air temperature for storage	-40...70 °C
Maximum pressure	158 Pa flow rate 0 m <sup>3</sup> /h
Connections - terminals	Faston connector

<b>IP degree of protection</b>	IP54
<b>Device composition</b>	1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template 1 power cord
<b>Condition of use</b>	Flow rates depends on the work point, see ProClima software Surrounding environment must be relatively clean Outside temperature must be 5 °C lower than inside temperature Filter must be cleaned and replaced regularly Overfrequent filter replacement should be avoided

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	18.5 cm
<b>Package 1 Width</b>	25 cm
<b>Package 1 Length</b>	27.5 cm
<b>Package 1 Weight</b>	1.72 kg
<b>Unit Type of Package 2</b>	P12
<b>Number of Units in Package 2</b>	64
<b>Package 2 Height</b>	120 cm
<b>Package 2 Width</b>	80 cm
<b>Package 2 Length</b>	120 cm
<b>Package 2 Weight</b>	126 kg

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>REACH free of SVHC</b>	Yes
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Recommended replacement(s)