	1   SI	SPSM-41T-M1.1	PSI CONNECTOR	R - MALE CONTACT						
	2 SI	SPSI-41T-M1.1	PSI CONNECTOR	R - FEMALE CONTACT						
	3 U	UL1007, 16 AWG	BLACK							
D								Applicable	e Housings	
"						NO. OF		FEMALE CONTACT	MALE CONTACT	
						CIRCUITS	KEYING	HOUSING PART NO.	HOUSING PART NO.	HOUSING COLOR
							Α	PSIP-02V-LE-A	PSIR-02V-LE-A	LIGHT BLUE
						2	В	PSIP-02V-Y-B	PSIR-02V-Y-B	YELLOW
							Α	PSIP-03V-LE-A	PSIR-03V-LE-A	LIGHT BLUE
						3	В	PSIP-03V-Y-B	PSIR-03V-Y-B	YELLOW
							7 +/- 5.0) 52.4 +/- 5.0			
						<	<			(2)
В					3					
В					3			E 1: 1 =	DESCRIPTION	
В					3		dime All	1:1	4.0 mm Pitch PSI Serie	
					3		DIME	1: 1 ENSIONS dimensions are in MM with a tolerance of +/- 3.0 unless otherwise specified. WN BY STEVEN PILKINGTON	4.0 mm Pitch PSI Serie DOUBI ASSEMBLY PART NO. ASF	es Standard Leads - 6" Inside LE-END LEADS, F-M PSISPSM16K152
	REV.		DESCRIPTION		3 DATE	BY	DIME All DRAV	1: 1 ENSIONS dimensions are in MM with a tolerance of +/- 3.0 unless otherwise specified. WN BY	4.0 mm Pitch PSI Serie DOUBI ASSEMBLY PART NO.	s Standard Leads - 6" Inside LE-END LEADS, F-M

2

3

DESCRIPTION

ок сноми without written permission. ۲ 5 7 ć

4

CONNECTOR PART NO.

ITEM

1