

Product data sheet

Specifications



Mechanical alternator, Square D Pumptrol, mech closed tank, NEMA 1, flange top mounted, 4 NC DPST DB contacts

9038DG7

Main

Range of product	Square D Pumptrol
Product or component type	Mechanical alternator
Device application	Top mounted closed tank
Device short name	9038D
Product specific application	Liquid level control
Electrical circuit type	Power circuit
Quantity per set	Set of 1
Type of packing	Individual

Complementary

Product destination	For open tank or sump
Device mounting	Flange
Cable entry number	8 knock-outs for 1/2" or 3/4"conduit conforming to UL 508
Contacts type and composition	4 NC, snap action, DPST-DB, Form YY
Controlled fluid	Fresh water at specific gravity of 0.85 in or higher -18...104 °C Sea water at specific gravity of 0.85 in or higher -18...104 °C Hydraulic oil at specific gravity of 0.85 in or higher -18...104 °C Corrosive fluid at specific gravity of 0.85 in or higher -18...104 °C
Motor power kW	1.5 kW (2 hp) at 115 V AC, 1 phase 2.2 kW (3 hp) at 115 V AC, 3 phases 2.2 kW (3 hp) at 230 V AC, 1 phase 3.7 kW (5 hp) at 230 V AC, 3 phases 0.75 kW (1 hp) at 460 V AC, 3 phases 0.75 kW (1 hp) at 475 V AC, 3 phases 0.18 kW (0.25 hp) at 32 V DC 0.37 kW (0.5 hp) at 115 V DC 0.37 kW (0.5 hp) at 230 V DC
Electrical connection	Screw-clamp terminals, clamping capacity: 10 AWG
Contact operation	Contacts close on liquid rise
Float movement	Variable fixed
Float position	Any
Float rod angle	Horizontal
Short-circuit protection	20 A cartridge fuse, type gG
Local signalling	Without
Materials in contact with fluid	Stainless steel 316 Stainless steel 304

Nitrile (Buna-N) or equivalent rubber
Yellow brass

Enclosure material	Painted cold-rolled steel
Operating position	Vertical position only
Electrical durability	100 cycles, operating rate <60 cyc/mn
Mechanical durability	300 cycles
Terminal block type	8 terminals
Maximum operating rate	60 cyc/mn
[Ui] rated insulation voltage	575 V conforming to UL 508
Terminals description ISO n°1	Line-load-load-line
Depth	113.54 mm
Width	173.74 mm
Factory modification	Without
Kit composition	Float switch Rod and float are to be chosen in accessories
Length	66.80 mm

Environment

Standards	UL 508 CE
Ambient air temperature for operation	-30...104 °C
Ambient air temperature for storage	-30...104 °C
NEMA degree of protection	NEMA 1 conforming to UL 50
Product certifications	UL listed file E12158 CSA file LR25490

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.6 cm
Package 1 Width	27.9 cm
Package 1 Length	31.2 cm
Package 1 Weight	3.7 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty 18 months

Recommended replacement(s)