

PRODUCT NUMBER	MATING LENGTH		POLARIZED PIN	
	DIM H	DIM H	AXX	BXX
	ENGLISH	METRIC		
10129383-XYY001XLF	0.230	5.84	—	—
10129383-XYY002XLF	0.318	8.08	—	—
10129383-XYY003XLF	0.230	5.84	A09	B09

PIN PLATING CODES:	
10129383-9YYXXXXLF	GOLD FLASH PLATING OVER 50u"/1.27u MIN Ni

NOTES:

- MATERIAL
 BODAY MATERIAL: HIGH TEMPERATURE THERMOPLASTIC.
 FLAME UL94-V0, BLACK.
 PIN MATERIAL: COPPER ALLOY.
- ANY NUMBER OF POSITIONS FROM 4(2X2) TO 40(2X20).
 PRODUCT MAYBE CUTTING TO POSITION,
 THE CUTTING PLASH IS 0.02[0.51] MAX.
- PACKING STYLE DEFINITION.
 B: PACKED WITH POLY BAG
 T: PACKED WITH TUBE
 A: PACKED WITH TAPE AND REEL WITH PICK UP CAP
 C: PACKED WITH TAPE AND REEL WITHOUT PICK UP CAP
- TWO SIDES OF PIN TIPS NOT PLATED, TYPICAL BOTH ENDS.
- 2LBS/0.9KG MIN PIN RETENTION IN EITHER DIRECTION BEFORE REFLOW.
- THE OAL DON'T EXCEED 1 INCH / 25.4MM.
- ADD LF AT THE END OF PART NUMBER IS FOR LEAD FREE.
- THESE PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER
 COUNTRY REGULATION AS DESCRIBED IN GS-22-008.
- THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE
 FOR 20 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.
- PRODUCT SPECIFICATION: GS-12-1223

Amphenol FCI

© 2016 AFCI

mat'l. code		surface		tolerance		projection		product family	
SEE NOTES 1		ISO 1302 ✓		ISO 406 ISO 1101				ECONOSTIK	
ltr	ecn	no	dr	date	tolerances unless otherwise specified		INCH/mm		title
D					angles	linear			ECONOSTIK HEADER
					X±2'	.xx±0.01/0.3	scale 2:1		.100/2.54cc DR SMT
					dr	ZK HU	04/23/14	dwg no	
					enr	MK XUAN	06/23/22	sheet 2 of 2	
					chr	LQ LEI	06/23/22	size	
					appd	TIM YAO	06/23/22	A4	
sheet	revision							type	
index	sheet							Product Customer Drawing	