


# LE RTB N7WM

## OSRAM OSTAR® Projection Compact

Compact lightsource in SMT technology, glass window on top, RoHS compliant



### Applications

- Augmented Reality, Mixed Reality
- Gaming, Amusement, Gambling
- Projection Mobile (LED & Laser)
- Virtual Reality

### Features:

- Package: compact lightsource in multi chip SMT technology with glass window on top
- Chip technology: Thinfilm / UX:3
- Typ. Radiation: 120° (Lambertian emitter)
- Color:  $\lambda_{\text{dom}} = 617 \text{ nm}$  (● red);  $\lambda_{\text{dom}} = 530 \text{ nm}$  (● true green);  $\lambda_{\text{dom}} = 465 \text{ nm}$  (● blue)
- ESD: 2 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)

---

## Ordering Information

| Type                                | Brightness <sup>1)</sup>   | Ordering Code |
|-------------------------------------|--|---------------|
| LE RTB N7WM-JXJZ-23+KXKZ-24+3T1U-35 |  | Q65112A4848   |
| • red                               | • $\Phi_V = 45 \dots 71 \text{ lm}$ ( $I_F = 350 \text{ mA}$ )   |               |
| • true green                        | • $\Phi_V = 71 \dots 112 \text{ lm}$ ( $I_F = 350 \text{ mA}$ )  |               |
| • blue                              | • $\Phi_E = 355 \dots 500 \text{ mW}$ ( $I_F = 350 \text{ mA}$ ) |               |

## Maximum Ratings

| Parameter   | Symbol         |      | Values  | Values       | Values  |
|---|----------------|------|---------|--------------|---------|
|   |                |      | ● red   | ● true green | ● blue  |
| Operating Temperature   | $T_{op}$       | min. | -40 °C  | -40 °C       | -40 °C  |
|   |                | max. | 85 °C   | 85 °C        | 85 °C   |
| Storage Temperature   | $T_{stg}$      | min. | -40 °C  | -40 °C       | -40 °C  |
|   |                | max. | 85 °C   | 85 °C        | 85 °C   |
| Junction Temperature  | $T_j$          | max. | 125 °C  | 125 °C       | 125 °C  |
| Forward Current<br>$T_j = T_{j\ max.}$                                    | $I_F$          | min. | 20 mA   | 20 mA        | 20 mA   |
|   |                | max. | 500 mA  | 500 mA       | 500 mA  |
| Forward Current pulsed<br>$D = 0.5 ; f = 240\ Hz ; T_j = 25\ ^\circ C$    | $I_{F\ pulse}$ |      | 1000 mA | 1000 mA      | 1000 mA |
| Surge Current<br>$t \leq 10\ \mu s ; D = 0.5 ; T_j = T_{j\ max.}$         | $I_{FS}$       | max. | 1500 mA | 1500 mA      | 1500 mA |
| ESD withstand voltage<br>acc. to ANSI/ESDA/JEDEC JS-001<br>(HBM, Class 2) | $V_{ESD}$      |      | 2 kV    | 2 kV         | 2 kV    |
| Reverse current <sup>2)</sup>   | $I_R$          | max. | 200 mA  | 200 mA       | 200 mA  |

## Characteristics

$I_F = 350 \text{ mA}$ ;  $T_J = 25 \text{ °C}$

| Parameter   | Symbol                  |      | Values                         | Values                         | Values                         |
|---|-------------------------|------|--------------------------------|--------------------------------|--------------------------------|
|   |                         |      | ● red                          | ● true green                   | ● blue                         |
| Peak Wavelength   | $\lambda_{\text{peak}}$ | typ. | 624 nm                         | 525 nm                         | 459 nm                         |
| Dominant Wavelength <sup>3)</sup>   | $\lambda_{\text{dom}}$  | min. | 610 nm                         | 518 nm                         | 455 nm                         |
|   |                         | typ. | 617 nm                         | 530 nm                         | 465 nm                         |
|   |                         | max. | 622 nm                         | 536 nm                         | 470 nm                         |
| Spectral bandwidth at 50% $I_{\text{rel,max}}$  | $\Delta\lambda$         | typ. | 18 nm                          | 35 nm                          | 18 nm                          |
| Viewing angle at 50% $I_V$  | $2\phi$                 | typ. | 120 °                          | 120 °                          | 120 °                          |
| Radiating surface   | $A_{\text{color}}$      | typ. | 0.65 x 0.65<br>mm <sup>2</sup> | 0.70 x 0.70<br>mm <sup>2</sup> | 0.70 x 0.70<br>mm <sup>2</sup> |
| Partial Flux acc. CIE 127:2007 <sup>4)</sup><br>$\Phi_{E/V 120^\circ} = x * \Phi_{E/V 180^\circ}$   | $\Phi_{E/V, 120^\circ}$ | typ. | 0.82                           | 0.82                           | 0.82                           |
| Forward Voltage <sup>5)</sup><br>$I_F = 350 \text{ mA}$   | $V_F$                   | min. | 1.90 V                         | 2.40 V                         | 2.70 V                         |
|   |                         | typ. | 2.30 V                         | 2.80 V                         | 2.95 V                         |
|   |                         | max. | 2.60 V                         | 3.30 V                         | 3.30 V                         |
| Reverse voltage (ESD device)  | $V_{R\text{ESD}}$       | min. | 45 V                           | 45 V                           | 45 V                           |
| Reverse voltage <sup>2)</sup><br>$I_R = 20 \text{ mA}$  | $V_R$                   | max. | 1.2 V                          | 1.2 V                          | 1.2 V                          |
| Real thermal resistance junction/solderpoint<br>Only one chip on at a time  | $R_{\text{thJS real}}$  | typ. | 15 K / W                       | 15 K / W                       | 15.0 K / W                     |
| Electrical thermal resistance junction/solderpoint<br>With efficiency:<br>red $\eta_e = 24\%$ ; green $\eta_e = 17\%$ ;<br>blue $\eta_e = 38\%$ | $R_{\text{thJS elec.}}$ | typ. | 11 K / W                       | 12 K / W                       | 9.3 K / W                      |

## Brightness Groups

- red

| Group | Luminous Flux <sup>1)</sup><br>$I_F = 350 \text{ mA}$<br>min.<br>$\Phi_V$ | Luminous Flux <sup>1)</sup><br>$I_F = 350 \text{ mA}$<br>max.<br>$\Phi_V$ |
|-------|---|---|
| JX    | 45 lm   | 52 lm   |
| JY    | 52 lm   | 61 lm   |
| JZ    | 61 lm   | 71 lm   |

## Brightness Groups

- true green

| Group | Luminous Flux <sup>3)</sup><br>$I_F = 350 \text{ mA}$<br>min.<br>$\Phi_V$ | Luminous Flux <sup>1)</sup><br>$I_F = 350 \text{ mA}$<br>max.<br>$\Phi_V$ |
|-------|---|---|
| KX    | 71 lm   | 82 lm   |
| KY    | 82 lm   | 97 lm   |
| KZ    | 97 lm   | 112 lm  |

## Brightness Groups

- blue

| Group | Radiant Flux <sup>1)</sup><br>$I_F = 350 \text{ mA}$<br>min.<br>$\Phi_E$ | Radiant Flux <sup>1)</sup><br>$I_F = 350 \text{ mA}$<br>max.<br>$\Phi_E$ |
|-------|--|--|
| 3T    | 355 mW   | 400 mW   |
| 4T    | 400 mW   | 450 mW   |
| 1U    | 450 mW   | 500 mW   |

## Wavelength Groups

- red

| Group | Dominant Wavelength <sup>3)</sup><br>min.<br>$\lambda_{\text{dom}}$ | Dominant Wavelength <sup>3)</sup><br>max.<br>$\lambda_{\text{dom}}$ |
|-------|---|---|
| 2     | 610 nm  | 616 nm  |
| 3     | 616 nm  | 622 nm  |

## Wavelength Groups

- true green

| Group | Dominant Wavelength <sup>3)</sup><br>min.<br>$\lambda_{\text{dom}}$ | Dominant Wavelength <sup>3)</sup><br>max.<br>$\lambda_{\text{dom}}$ |
|-------|---|---|
| 2     | 518 nm  | 524 nm  |
| 3     | 524 nm  | 530 nm  |
| 4     | 530 nm  | 536 nm  |

## Wavelength Groups

- blue

| Group | Dominant Wavelength <sup>3)</sup><br>min.<br>$\lambda_{\text{dom}}$ | Dominant Wavelength <sup>3)</sup><br>max.<br>$\lambda_{\text{dom}}$ |
|-------|---|---|
| 3     | 455 nm  | 460 nm  |
| 4     | 460 nm  | 465 nm  |
| 5     | 465 nm  | 470 nm  |


## Group Name on Label

Example: 1U-3+KX-2+JX-2

| Color        | Brightness | Wavelength |
|--------------|------------|------------|
| • red        | JX         | 2          |
| • true green | KX         | 2          |
| • blue       | 1U         | 3          |


### Relative Spectral Emission <sup>4)</sup>

$\Phi_{rel} = f(\lambda); I_F = 350 \text{ mA}; T_J = 25 \text{ }^\circ\text{C}$




### Radiation Characteristics <sup>4)</sup>

$I_{rel} = f(\phi); T_J = 25 \text{ }^\circ\text{C}$



**Relative Partial Flux** <sup>4)</sup>


$$\Phi_{EM}(2\varphi) / \Phi_{EM}(180^\circ) = f(\varphi); T_j = 25^\circ\text{C}$$






**Forward current** 4), 6)

$I_F = f(V_F); T_J = 25\text{ °C}$




**Forward current** 4), 6)

$I_F = f(V_F); T_J = 25\text{ °C}$




**Forward current** 4), 6)

$I_F = f(V_F); T_J = 25\text{ °C}$




**Relative Luminous Flux** 4), 6)

$$\Phi_V / \Phi_V(350 \text{ mA}) = f(I_F); T_J = 25 \text{ }^\circ\text{C}$$




**Relative Luminous Flux** 4), 6)

$$\Phi_V / \Phi_V(350 \text{ mA}) = f(I_F); T_J = 25 \text{ }^\circ\text{C}$$




**Relative Radiant Power** 4), 6)

$$\Phi_E / \Phi_E(350 \text{ mA}) = f(I_F); T_J = 25 \text{ }^\circ\text{C}$$




### Dominant Wavelength <sup>4)</sup>

$$\Delta\lambda_{\text{dom}} = f(I_F); T_J = 25\text{ }^\circ\text{C}$$




### Dominant Wavelength <sup>4)</sup>

$$\Delta\lambda_{\text{dom}} = f(I_F); T_J = 25\text{ }^\circ\text{C}$$




**Forward Voltage** <sup>4)</sup>

$$\Delta V_F = V_F - V_F(25\text{ }^\circ\text{C}) = f(T_j); I_F = 350\text{ mA}$$




**Forward Voltage** <sup>4)</sup>

$$\Delta V_F = V_F - V_F(25\text{ }^\circ\text{C}) = f(T_j); I_F = 350\text{ mA}$$




**Forward Voltage** <sup>4)</sup>

$$\Delta V_F = V_F - V_F(25\text{ }^\circ\text{C}) = f(T_j); I_F = 350\text{ mA}$$




**Relative Luminous Flux** <sup>4)</sup>

$\Phi_V / \Phi_V(25\text{ °C}) = f(T_j); I_F = 350\text{ mA}$




**Relative Luminous Flux** <sup>4)</sup>

$\Phi_V / \Phi_V(25\text{ °C}) = f(T_j); I_F = 350\text{ mA}$




**Relative Radiant Power** <sup>4)</sup>

$\Phi_E / \Phi_E(25\text{ °C}) = f(T_j); I_F = 350\text{ mA}$




### Dominant Wavelength <sup>4)</sup>

$$\Delta\lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25\text{ °C}) = f(T_j); I_F = 350\text{ mA}$$




### Dominant Wavelength <sup>4)</sup>

$$\Delta\lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25\text{ °C}) = f(T_j); I_F = 350\text{ mA}$$





### Dominant Wavelength <sup>4)</sup>

$$\Delta\lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25\text{ °C}) = f(T_j); I_F = 350\text{ mA}$$



## Dimensional Drawing <sup>7)</sup>



general tolerance  $\pm 0.1$   
 lead finish Au 


C67062-A0229-A1 -01

## Further Information:

**Approximate Weight:** 60.0 mg

**ESD advice:** The device is protected by ESD device which is connected in parallel to the Chip.


## Electrical Internal Circuit



| Pin    | Description |
|--------|-------------|
| Chip 1 | blue        |
| Chip 2 | true green  |
| Chip 3 | red         |



Recommended Solder Pad 7)




E062 3010.101-01

Do not use exposed copper MCPCB technology. For superior solder joint connectivity results we recommend soldering under standard nitrogen atmosphere. Package not suitable for any kind of wet cleaning or ultrasonic cleaning.

## Reflow Soldering Profile

Product complies to MSL Level 2 acc. to JEDEC J-STD-020E





| Profile Feature  | Symbol | Pb-Free (SnAgCu) Assembly |                |         | Unit |
|--|--------|---------------------------|----------------|---------|------|
|  |        | Minimum                   | Recommendation | Maximum |      |
| Ramp-up rate to preheat <sup>*)</sup><br>25 °C to 150 °C       |        |                           | 2              | 3       | K/s  |
| Time $t_s$<br>$T_{Smin}$ to $T_{Smax}$                         | $t_s$  | 60                        | 100            | 120     | s    |
| Ramp-up rate to peak <sup>*)</sup><br>$T_{Smax}$ to $T_p$      |        |                           | 2              | 3       | K/s  |
| Liquidus temperature   | $T_L$  |                           | 217            |         | °C   |
| Time above liquidus temperature                                | $t_L$  |                           | 80             | 100     | s    |
| Peak temperature   | $T_p$  |                           | 245            | 260     | °C   |
| Time within 5 °C of the specified peak temperature $T_p - 5$ K | $t_p$  | 10                        | 20             | 30      | s    |
| Ramp-down rate*<br>$T_p$ to 100 °C                             |        |                           | 3              | 6       | K/s  |
| Time<br>25 °C to $T_p$   |        |                           |                | 480     | s    |

All temperatures refer to the center of the package, measured on the top of the component


\* slope calculation  $DT/Dt$ :  $Dt$  max. 5 s; fulfillment for the whole T-range

Taping <sup>7)</sup>



C67062-A0229-B6-01

**Tape and Reel** <sup>8)</sup>



**Reel Dimensions**

| A      | W                   | N <sub>min</sub> | W <sub>1</sub> | W <sub>2max</sub> | Pieces per PU |
|--------|---------------------|------------------|----------------|-------------------|---------------|
| 180 mm | 12 + 0.3 / - 0.1 mm | 60 mm            | 12.4 + 2 mm    | 18.4 mm           | 500           |

## Barcode-Product-Label (BPL)

**OSRAM Opto Semiconductors** LX XXXX    BIN1: XX-XX-X-XXX-X


RoHS Compliant

(6P) BATCH NO: 1234567890 ML Temp    ST  
X    XXX °C X

(1T) LOT NO: 1234567890 (9D) D/C: 1234


(X) PROD NO: 123456789(Q)QTY: 9999 (G) GROUP: XX-XX-X-X

Pack: RXX  
DEMY    XXX  
X\_X123\_1234.1234 X



OHA04563

## Dry Packing Process and Materials <sup>7)</sup>



OHA00539

Moisture-sensitive product is packed in a dry bag containing desiccant and a humidity card according JEDEC-STD-033.

## Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the device specified in this data sheet fall into the class **moderate risk (exposure time 0.25 s)**. Under real circumstances (for exposure time, conditions of the eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. When looking at bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

For further application related information please visit [www.osram-os.com/appnotes](http://www.osram-os.com/appnotes)

## Disclaimer

### **Attention please!**

The information describes the type of component and shall not be considered as assured characteristics. Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact our Sales Organization.

If printed or downloaded, please find the latest version on the OSRAM OS website.

### **Packing**

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

### **Product and functional safety devices/applications or medical devices/applications**

OSRAM OS components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.

OSRAM OS products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using OSRAM OS components in product safety devices/applications or medical devices/applications, buyer and/or customer has to inform the local sales partner of OSRAM OS immediately and OSRAM OS and buyer and /or customer will analyze and coordinate the customer-specific request between OSRAM OS and buyer and/or customer.

---

## Glossary

- 1) **Brightness:** Brightness values are measured during a current pulse of typically 25 ms, with an internal reproducibility of  $\pm 8\%$  and an expanded uncertainty of  $\pm 11\%$  (acc. to GUM with a coverage factor of  $k = 3$ ).
- 2) **Reverse Operation:** This product is intended to be operated applying a forward current within the specified range. Applying any continuous reverse bias or forward bias below the voltage range of light emission shall be avoided because it may cause migration which can change the electro-optical characteristics or damage the LED.
- 3) **Wavelength:** The wavelength is measured at a current pulse of typically 25 ms, with an internal reproducibility of  $\pm 0.5$  nm and an expanded uncertainty of  $\pm 1$  nm (acc. to GUM with a coverage factor of  $k = 3$ ).
- 4) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.
- 5) **Forward Voltage:** The forward voltage is measured during a current pulse of typically 8 ms, with an internal reproducibility of  $\pm 0.05$  V and an expanded uncertainty of  $\pm 0.1$  V (acc. to GUM with a coverage factor of  $k = 3$ ).
- 6) **Characteristic curve:** In the range where the line of the graph is broken, you must expect higher differences between single devices within one packing unit.
- 7) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with  $\pm 0.1$  and dimensions are specified in mm.
- 8) **Tape and Reel:** All dimensions and tolerances are specified acc. IEC 60286-3 and specified in mm.



---

## Revision History

| Version | Date       | Change   |
|---------|------------|--|
| 1.2     | 2018-11-29 | Characteristics  |
| 1.4     | 2019-07-31 | Wavelength Groups  |
| 1.6     | 2019-12-10 | Further Information  |
| 1.6     | 2019-12-10 | Further Information  |
| 1.7     | 2020-06-03 | Schematic Transportation Box<br>Dimensions of Transportation Box |
| 1.8     | 2020-11-20 | Product Image<br>Characteristics                                 |
| 1.9     | 2020-12-16 | Characteristics  |
| 1.10    | 2021-04-12 | Ordering Information<br>Brightness Groups                        |

---

Published by OSRAM Opto Semiconductors GmbH EU RoHS and China RoHS compliant product  
Leibnizstraße 4, D-93055 Regensburg  
www.osram-os.com © All Rights Reserved.



此产品符合欧盟 RoHS 指令的要求；  
按照中国的相关法规和标准，不含有毒有害物质或元素。