160859-5 - ACTIVE

FASTIN-FASTON | FASTIN-FASTON 250

TE Internal #: 160859-5 Quick Disconnects, Tab, 20 – 17 AWG Wire Size, .51 – 1.03 mm² Wire Size, Mating Tab Width 6.35 mm [.25 in], Straight, FASTIN-FASTON 250

View on TE.com >

Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: Tab

Wire Size: .51 – 1.03 mm²

Mating Tab Width: 6.35 mm [.25 in]

Mating Tab Thickness: .81 mm [.032 in]

Features

Product Type Features



| Insertion Force | Normal |
|-----------------------------------|-----------------|
| Configuration Features | |
| Connection Capacity | Single |
| Compatible With Wire & Cable Type | Discrete Wire |
| Contact Features | |
| Quick Disconnect Terminal Type | Tab |
| Mating Tab Width | 6.35 mm[.25 in] |
| Mating Tab Thickness | .81 mm[.032 in] |
| Terminal Orientation | Straight |
| Contact Base Material | Phosphor Bronze |
| Terminal Plating Material | Silver |
| Crimp Type | F-Crimp |
| Barrel Type | Open |
| Termination Features | |

C For support call+1 800 522 6752

160859-5

Quick Disconnects, Tab, 20 – 17 AWG Wire Size, .51 – 1.03 mm² Wire Size, Mating Tab Width 6.35 mm [.25 in], Straight, FASTIN-FASTON 250



| Product Terminates To | Wire & Cable |
|--------------------------------------|-----------------------------|
| Mechanical Attachment | |
| Locking Lance Height | 1.44 mm |
| Wire Insulation Support | With |
| Mating Retention Type | Locking Lance |
| Dimensions | |
| Terminal Material Thickness | .41 mm[.016 in] |
| Product Length | 28 mm[1.1 in] |
| Compatible Insulation Diameter Range | 1.4 – 2.3 mm[.055 – .09 in] |
| Wire Size | .51 – 1.03 mm² |
| Usage Conditions | |
| Insulation Option | Uninsulated |
| Operating Temperature Range | -40 – 130 °C[-40 – 266 °F] |
| Packaging Features | |
| Packaging Quantity | 3500 |
| Packaging Method | Strip/Reel |
| Other | |

Terminals & Splices Comment

According to DIN 46343, Part 3, With locking hole.

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not applicable for solder process capability |

160859-5


Quick Disconnects, Tab, 20 – 17 AWG Wire Size, .51 – 1.03 mm² Wire Size, Mating Tab Width 6.35 mm [.25 in], Straight, FASTIN-FASTON 250



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | FASTIN-FASTON 250




Customers Also Bought

160859-5

Quick Disconnects, Tab, 20 – 17 AWG Wire Size, .51 – 1.03 mm² Wire Size, Mating Tab Width 6.35 mm [.25 in], Straight, FASTIN-FASTON 250





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_160859-5_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_160859-5_L.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_160859-5_L.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 1654742_HOUSEHOLD_APPLIANCES_RAST5

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English