



DESIGNED FOR USE WITH	RG-188/U
CABLE ENTRY DIAMETER	MINIMUM
CONTACT	.021
DIELECTRIC	.023
SLEEVE	.066
FERRULE	.125

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₂	REVISED	9/13/86	[Signature]

COMPONENT	MATERIAL	FINISH
HOUSING CLAMP NUT SLEEVE	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
O-RING	SILICONE RUBBER PER ZZ-R-765	N/A
SHRINK TUBING	HEAT SHRINKABLE POLYOLEFIN COMPOUND MIL-I-23053/4	N/A
FERRULE	COPPER OR BRASS ALLOY ROCKWELL F65 MAXIMUM	GOLD PLATE PER MIL-G-45204

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY FMC	DATE 9/15/77	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	CHECKED BY KWW	9/21/77	
	APPD BY RMF	9/21/77	

These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	TITLE "OSM" STRAIGHT CABLE JACK CRIMP-CLAMP ATTACHMENT	
	NO. A.P. 408-04808 (20-057)	SIZE B	CODE IDENT NO. 26805
		SCALE 5:1	2032-5003-02

NOTES:
1. CAPTURED CENTER CONTACT

.XXX = in
XX.X = mm (REF)