



2/1/80

000209

USS 1702/1220

description

These devices contain four independent 2-input NAND gates. They perform the boolean functions $Y = \overline{A} \cdot \overline{B}$ or $Y = \overline{A} + \overline{B}$ in positive logic. The open-collector outputs require pull-up resistors to perform correctly. They may be connected to other open-collector outputs to implement active-low wired-OR or active-high wired-AND functions. Open-collector devices are often used to generate higher V_{OH} levels.

The SN54ALS03 is characterized for operation over the full military temperature range of -55°C to 125°C . The SN74ALS03 is characterized for operation from 0°C to 70°C .

(TOP VIEW)


1A	1	14	VCC
1B	2	13	4B
1Y	3	12	4A
2A	4	11	4Y
2B	5	10	3B
2Y	6	9	3A
GND	7	8	3Y

J Suffix—Case 632-07 (Ceramic)
N Suffix—Case 646-05 (Plastic)

FUNCTION TABLE (each gate)

INPUTS		OUTPUT
A	B	Y
H	H	L
L	X	H
X	L	H

logic symbol



Pin numbers shown are for J and N packages.

TYPES SN54ALS03, SN74AL03
QUADRUPLE 2-INPUT POSITIVE-NAND GATES
WITH OPEN-COLLECTOR OUTPUTS

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V _{CC}	7 V
Input voltage	7 V
Off-state output voltage	7 V
Operating free-air temperature range: SN54ALS03	- 55°C to 125°C
SN74ALS03	0°C to 70°C
Storage temperature range	- 65°C to 150°C

recommended operating conditions

		SN54ALS03			SN74ALS03			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V _{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V _{IH}	High-level input voltage	2			2			V
V _{IL}	Low-level input voltage			0.8			0.8	V
V _{OH}	High-level output voltage			5.5			5.5	V
I _{OL}	Low-level output current			4			8	mA
T _A	Operating free-air temperature	- 55		125	0		70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54ALS03			SN74ALS03			UNIT
		MIN	TYP‡	MAX	MIN	TYP‡	MAX	
V _{IK}	V _{CC} = 4.5 V, I _I = - 18 mA			- 1.5			- 1.5	V
I _{OH}	V _{CC} = 4.5 V, V _{OH} = 5.5 V			0.1			0.1	mA
V _{OL}	V _{CC} = 4.5 V, I _{OL} = 4 mA		0.25	0.4	0.25	0.4		V
	V _{CC} = 4.75 V, I _{OL} = 8 mA					0.35	0.5	
I _I	V _{CC} = 5.5 V, V _I = 7 V			0.1			0.1	mA
I _{IH}	V _{CC} = 5.5 V, V _I = 2.7 V			20			20	µA
I _{IL}	V _{CC} = 5.5 V, V _I = 0.4 V		- 0.1			- 0.1		mA
I _{CCH}	V _{CC} = 5.5 V, V _I = 0 V			0.8			0.8	mA
I _{CCL}	V _{CC} = 5.5 V, V _I = 4.5 V			2.2			2.2	mA

‡All typical values are at V_{CC} = 5 V, T_A = 25°C

switching characteristics

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 5 V, C _L = 15 pF, R _L = 2 kΩ, T _A = 25°C	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 2 kΩ, T _A = MIN to MAX	UNIT			
			'ALS03	SN54ALS03				
			TYP	MIN	MAX			
t _{PLH}	A or B	Y	8	3	20	3	15	ns
t _{PHL}	A or B	Y	12	5	26	5	22	ns

Motorola reserves the right to make changes to any products herein to improve reliability, function or design. Motorola does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights nor the rights of others.



MOTOROLA Semiconductor Products Inc.

PO. BOX 20912 • PHOENIX, ARIZONA 85036 • A SUBSIDIARY OF MOTOROLA INC.