



NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0; GREEN
3. SIGNAL CONTACTS: COPPER ALLOY
PLATING: 30µin HARD GOLD over min. 50µin NICKEL
4. NO CONTACT ON POS A1
5. CONNECTOR IS PART MARKED: 3047W1SCM99A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GmbH
 DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name
a	Origin		



tolerance	\varnothing \pm	scale:	2:1 (5:1)	
	dim. in mm	material:	SEE NOTES	
date	name	title: D-SUB COMBINATION FEMALE 47W1S SOLDER CUP		
drawn 30.04.2010	Henneboel			
appd. 03.05.2010	Koch			
norm		dwg no:	Inventor 10	DIN-A3
d-old				sh: 1
		part no: 3047W1SCM99A10X		