

- Products**
- Products Overview
  - Product Search**
  - Evaluate
    - FAQ's
  - Design a Solution
    - Part Drawings
    - PDF-Right Angle ..
  - How to Buy
    - Bill of Material
    - Favorite Products List
    - Locate Distributor

Home > Products Overview > Product Search >

Current refinements (click  to remove) [Search Tips](#)

Part Number > DNFR14-250B-L

Your search criteria matched only one product, shown below

### DNFR14-250B-L

- Right angle design for use in limited space applications
- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Disconnects available in common industry tab sizes
- Longer barrel design for use with Panduit standard disconnect tool



Part Number	DNFR14-250B-L
RoHS Compliancy Status	Compliant
Note	DNFR14-250B-L replaces DNFR14-250B-C
Part Description	Female Disconnect, right angle, nylon insulated, 16 – 14 AWG, .250 x .032 tab size.
Product Type	Disconnects
CSA Certified	Yes
UL Listed	Yes
Depth (In.)	0.63
Depth (mm)	16.0
Height (In.)	0.20
Height (mm)	5.1
Length (In.)	0.78
Length (mm)	19.8
Width (In.)	0.36
Width (mm)	9.1
CE Compliant	No
Max. Ins.	0.155
Max. Ins. (mm)	3.95
Panduit Color Code	Blue
Pricing Description	Female Disconnect, right angle, nylon insulated, 16 - 14 AWG, .250 x .032 tab size
Tab Size (In.)	0.250 x 0.032
Tab Size (mm)	6.3 x 0.8
Tool	CT-1525‡, CT-2500‡
Wire Range	16 – 14 AWG
Wire Range (mm²)	1.5 – 2.5
Min. Order UOM	PC
Min. Order Qty.	50
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.