2 METERS LENGTH



Connector A 132119 SMA Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B FA1-NZSJ-C01-0 FAKRA Jack Straight Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

	Connector A			Cable		Connector B		
Part #: Descripti Type: Gender: Body Typ Contact Polarity: Impedan: Mounting Body Ma Body Fin IP Rating Contact I Contact I Max. Free Booting:	SMA Jack Jack Straight Type: Solder Standard ce: 50 Ohm g: Bulkhead - Rear terial: Brass ish: Gold I: None Material: Beryllium Copper Finish: Gold q.: 12.4 GHz	SMA BHD JK RG174 RG188 RG316 500 SMA Jack Straight Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None al: Beryllium Copper Gold		RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 2 Meters	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	FA1-NZSJ-C01-0 FAKRA-Z JK RG174 FAKRA Jack Straight Crimp Standard 50 Ohm Cable Brass Nickel None Beryllium Copper Gold 3 GHz FAKRA-Z Jack Stra 0°		
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT - DO NOT COPY		THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		BLE ED F ING Part No:	SMA-ST-JK/FKRAZ-ST-JK G174 2M		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	