

# SAC-3P-22AWG-OE-OE-544-300,0SH - Cable reel



1318412

<https://www.phoenixcontact.com/us/products/1318412>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



By the meter, Cable reel, shielded, PVC, gray, 3-wire, color single wire: brown, blue, black, cable length: 300 m

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1318412       |
| Packing unit                         | 1 pc          |
| Sales key                            | BF16          |
| Product key                          | BF1IIB        |
| GTIN                                 | 4063151600099 |
| Weight per piece (including packing) | 22.22 g       |
| Weight per piece (excluding packing) | 22.22 g       |
| Country of origin                    | US            |

# SAC-3P-22AWG-OE-OE-544-300,0SH - Cable reel



1318412

<https://www.phoenixcontact.com/us/products/1318412>

## Technical data


### Product properties

|                     |                    |
|---------------------|--------------------|
| Product type        | Cable by the meter |
| Number of positions | 3                  |
| Application         | Connector          |

### Cable/line

|              |       |
|--------------|-------|
| Cable length | 300 m |
|--------------|-------|

PVC gray 105 °C [544]

|   |   |
|---|---|
| Dimensional drawing                           |  |
| Cable weight                                  | 40 kg/km  |
| UL AWM Style                                  | 2517 (105 °C / 300 V)   |
| Number of positions                           | 3   |
| Shielded                                      | yes   |
| Cable type                                    | PVC gray 105 °C [544]   |
| Conductor structure signal line               | 30x 1.30 mm   |
| AWG signal line                               | 22  |
| Wire diameter incl. insulation                | 1.27 mm ±0.03 mm  |
| External cable diameter                       | 5.2 mm ±0.2 mm  |
| Outer sheath, material                        | PVC   |
| External sheath, color                        | gray  |
| Conductor material                            | Tin-plated Cu litz wires  |
| Material wire insulation                      | PVC   |
| Single wire, color                            | brown, blue, black  |
| Overall twist                                 | 3 wires, twisted  |
| Optical shield covering                       | 85 %  |
| Max. conductor resistance                     | max. 50.5 Ω/km (20 °C)  |
| Insulation resistance                         | ≥ (550 M Ohms/m @ 500V)   |
| Nominal voltage, cable                        | 300 V   |
| Minimum bending radius, flexible installation | 12 x D  |
| Flame resistance                              | FT4   |
| Other resistance                              | UV resistant  |
| Special properties                            | UL standards PLTC and ITC   |
| Ambient temperature (operation)               | -30 °C ... 105 °C (cable, fixed installation)                                       |

# SAC-3P-22AWG-OE-OE-544-300,0SH - Cable reel



1318412

<https://www.phoenixcontact.com/us/products/1318412>

---

-5 °C ... 105 °C (Cable, flexible installation)

# SAC-3P-22AWG-OE-OE-544-300,0SH - Cable reel



1318412

<https://www.phoenixcontact.com/us/products/1318412>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27061801 |
| ECLASS-12.0 | 27061801 |
| ECLASS-13.0 | 27061801 |

# SAC-3P-22AWG-OE-OE-544-300,0SH - Cable reel



1318412

<https://www.phoenixcontact.com/us/products/1318412>

## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

# SAC-3P-22AWG-OE-OE-544-300,0SH - Cable reel



1318412

<https://www.phoenixcontact.com/us/products/1318412>

## Accessories

### WIREFOX SAC - Stripping tool

1212623

<https://www.phoenixcontact.com/us/products/1212623>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

---

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)