0.5 METER LENGTH





Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B SMP-FR-C08-1 SMP Plug Right Angle Beryllium Copper Gold + Heatshrink

Connector B

Assembly & Label Notes

Connector A

Assembly label to be placed \sim 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.



2245 //A R/A BHD JK RG174 RG316 LMR100	Part #:	RG-174	Don't #	0MD ED 000 4
/IA R/A BHD JK RG174 RG316 LMR100		110-114	Part #:	SMP-FR-C08-1
	Description:	RG-174 - PE 0.1	Description:	SMP R/A PLUG RG316 RG174 500
0	Dielectric:	PE	Type:	SMP
ЛA	Shielding:	Braid	Gender:	Plug
ck	Diameter:	0.1	Body Type:	Right Angle
ght Angle	Impedance:	50 Ohm	Contact Type:	Solder
older	Sheathing:	None	Polarity:	Standard
andard	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm
Ohm	Length:	0.5 Meter	Mounting:	Cable
ılkhead - Rear Mount			Body Material:	Beryllium Copper
ass			Body Finish:	Gold
old			IP Rating:	None
one			Contact Material:	Beryllium Copper
eryllium Copper			Contact Finish:	Gold
old			Max. Freg.:	26.5 GHz
.4 GHz			· ·	SMP Plug Right Angle
//A Jack Right Angle			Clocking:	0°
	MA ck ght Angle Ider andard Ohm Ikhead - Rear Mount ass Id ne ryllium Copper Id 4 GHz	MA Shielding: Diameter: Impedance: Impedance: Sheathing: Testing: Length: Idd Ine Inguilium Copper Idd Inguilium Copper Inguilium	Shielding: Braid Diameter: 0.1 Impedance: 50 Ohm Ider Inder	Shielding: Braid Ck Ch Diameter: 0.1 Impedance: 50 Ohm Impedance: Impedance

Cable



THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-RA-JK/SMP-RA-PL G174 0.5M

Part No:

Q-2P04200030.5M

UNLESS SPECIFIED

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES