



all dimensions in mm

|   |            |
|---|------------|
| d | 1.45 nom   |
| e | 12.25±0.30 |
| f | 5.5±1.0    |

|       |       |      |      |   |
|-------|-------|------|------|---|
| a1    | a2    | b1   | b2   | h |
| d+0.5 | d+1.0 | 0.25 | 0.25 | 7 |

|                         |      |
|-------------------------|------|
| Halogen bulb            |      |
| H2 12V 100W Rally       |      |
| Cap: <sup>1)</sup> X511 |      |
| Type: RA                |      |
| ECE R37                 | None |
| FMVSS108                | None |
| Bulb mat.: Quartz glass |      |
| Made in korea / INCHEON |      |

1) according to IEC 61-1 sheet 7004-99-2

|                    |              |
|--------------------|--------------|
| Technical data     |              |
| Test voltage       | 13.2V        |
| Power              | 85W max.     |
| Luminous flux      | 2000lm ± 15% |
| Lumen maintenance  | 90 % min     |
| Rated life:        | at 13.2V     |
| -characteristic Tc | 200 h min    |
| -B3                | 90 h min     |

|                                |                                       |
|--------------------------------|---------------------------------------|
| Maximum operating temperature: | 1:bulb 800°C max<br>2:pinch 400°C max |
|--------------------------------|---------------------------------------|