



**NOTES:**

- METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
- INSULATORS: PBT GF UL 94 V-0, GREEN
- SIGNAL CONTACTS: COPPER ALLOY  
PLATING: GOLD FLASH over NICKEL
- NO CONTACTS ON POS. A1 - A4
- CONNECTOR IS PART MARKED: 3009W4SAR99A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance		dim. in mm	scale: 2:1 (5:1)			
							material: SEE NOTES			
						date	name		title: <b>D-SUB COMBINATION FEMALE (b)</b> 9W4S	
						drawn	11.05.11 Heneboel			
		appd.	11.05.11 Koch							
		norm		d-old		dwg no: Inventor 10				
1 x b		A3999	12.05.2011	K.H.		DIN-A3				
a		Original				sh: 1				
rev.		description date name				part no: 3009W4SAR99A10X				