

## **Specification Sheet**

Part Number: 155-30902



Clip can be installed by hand – no need for hardware or tools.

Design provides low insertion and high extraction force, for simple, secure performance.

Clip keeps bundle away from areas that could cause damage due to rubbing.

Article Number 155-30902

Type SOC4MFT6

Color Black (BK)

Quantity Per bag

Product Description Bundling clips are designed to provide simple and easy methods of

securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using bundle or cable ties. The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standard bundling clips are available as well as

standoff and stud mount versions.

Short Description Standoff Bundling Clip, 2.2" Long, Panel Thickness .02 - .03",

PA66HIRHS, Black, 500/box

| Length L (Imperial)                     | 2.2          |
|---|--------------|
| Length L (Metric)                       | 55.0         |
| Offset Length (Imperial)                | 0.79         |
| Offset Length (Metric)                  | 20.0         |
| Fixation Method                         | Fir Tree     |
| Width W (Metric)                        | 20.0         |
| Height H (Imperial)                     | 0.54         |
| Height H (Metric)                       | 13.7         |
| Panel Thickness Min (Imperial)          | 0.03         |
| Panel Thickness Max (Imperial)          | 0.2          |
| Panel Thickness Min (Metric)            | 0.7          |
| Panel Thickness Max (Metric)            | 5.1          |
| Mounting Hole Diameter D (Imperial)     | 0.25 - 0.28  |
| Mounting Hole Diameter D (Metric)       | 6.5 - 7.0 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.283        |

Mounting Hole Diameter D Max (Imperial) 0.28

Mounting Hole Diameter D Max (Metric) 7.0

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL 94 HB

UV Resistant (Yes/No) No

ov resistant (165/140)

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach

| to product design, sustainability, producustomers. HellermannTyton operates ( <a href="https://www.hellermann.tyton.com">www.hellermann.tyton.com</a> ). |            |                      |            |                      |
|--|------------|----------------------|------------|----------------------|
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
| © 2023 HellermannTyton. All Rights   | Posorvod   |                      |            |                      |
| © 2023 Hellermann Tyton. All Nights  | Contact Us | RoHS/WEEE Compliance | Disclaimer | Terms and Conditions |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |
|  |            |                      |            |                      |