## 48 INCHES LENGTH



Connector A 132117RP SMA Jack Straight Brass Gold + Heatshrink 50 Ohm RG-316 Continuity/Hi-Pot Connector B 034-5019 HD-BNC Jack Straight Bulkhead - Rear Mount Brass Nickel + Heatshrink

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Part #: 132117RP   Description: SMA JACK RP RG3   Type: SMA   Gender: Jack   Body Type: Straight   Contact Type: Crimp   Polarity: Reverse   Impedance: 50 Ohm   Mounting: Cable   Body Material: Brass   Body Finish: Gold   IP Rating: None   Contact Finish: Gold   Max. Freq.: 12.4 GHz   Booting: SMA Jack Straight I	Part #: 316 500 Description:			Connector B	
Type: SMA   Gender: Jack   Body Type: Straight   Contact Type: Crimp   Polarity: Reverse   Impedance: 50 Ohm   Mounting: Cable   Body Material: Brass   Body Finish: Gold   IP Rating: None   Contact Material: Brass   Contact Material: Brass   Contact Material: Brass   Contact Finish: Gold   Max. Freq.: 12.4 GHz   Booting: SMA Jack Straight I	316.500 Description:	RG-316	Part #:	034-5019	
Gender: Jack Gender: Jack Body Type: Straight Contact Type: Crimp Polarity: Reverse Impedance: 50 Ohm Mounting: Cable Body Material: Brass Body Finish: Gold IP Rating: None Contact Material: Brass Contact Finish: Gold Max. Freq.: 12.4 GHz Booting: SMA Jack Straight I		RG-316 - ST 0.102	Description:	HD-BNC BHD JK RG316 500	
Body Type: Straight   Contact Type: Crimp   Polarity: Reverse   Impedance: 50 Ohm   Mounting: Cable   Body Material: Brass   Body Finish: Gold   IP Rating: None   Contact Finish: Gold   Max. Freq.: 12.4 GHz   Booting: SMA Jack Straight I	Dielectric:	ST	Type:	HD-BNC	
Contact Type: Crimp   Polarity: Reverse   Impedance: 50 Ohm   Mounting: Cable   Body Material: Brass   Body Finish: Gold   IP Rating: None   Contact Material: Brass   Contact Material: Brass   Contact Material: Brass   Contact Finish: Gold   Max. Freq.: 12.4 GHz   Booting: SMA Jack Straight I	Shielding:	Braid	Gender:	Jack	
Polarity: Reverse   Impedance: 50 Ohm   Mounting: Cable   Body Material: Brass   Body Finish: Gold   IP Rating: None   Contact Material: Brass   Contact Tinish: Gold   Max. Freq.: 12.4 GHz   Booting: SMA Jack Straight I	Diameter:	0.102	Body Type:	Straight	
Polarity: Reverse   Impedance: 50 Ohm   Mounting: Cable   Body Material: Brass   Body Finish: Gold   IP Rating: None   Contact Material: Brass   Contact Tinish: Gold   Max. Freq.: 12.4 GHz   Booting: SMA Jack Straight I	Impedance:	50 Ohm	Contact Type:	Solder	
Impedance: 50 Ohm   Mounting: Cable   Body Material: Brass   Body Finish: Gold   IP Rating: None   Contact Material: Brass   Contact Finish: Gold   Max. Freq.: 12.4 GHz   Booting: SMA Jack Straight I	Sheathing:	None	Polarity:	Standard	
Body Material: Brass Body Finish: Gold IP Rating: None Contact Material: Brass Contact Finish: Gold Max. Freq.: 12.4 GHz Booting: SMA Jack Straight I	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm	
Body Material: Brass   Body Finish: Gold   IP Rating: None   Contact Material: Brass   Contact Finish: Gold   Max. Freq.: 12.4 GHz   Booting: SMA Jack Straight I	Length:	48 Inches	Mounting:	Bulkhead - Rear Mount	
Body Finish: Gold   IP Rating: None   Contact Material: Brass   Contact Finish: Gold   Max. Freq.: 12.4 GHz   Booting: SMA Jack Straight I			Body Material:	Brass	
IP Rating: None Contact Material: Brass Contact Finish: Gold Max. Freq.: 12.4 GHz Booting: SMA Jack Straight I			Body Finish:	Nickel	
Contact Material: Brass Contact Finish: Gold Max. Freq.: 12.4 GHz Booting: SMA Jack Straight I			IP Rating:	None	
Contact Finish: Gold Max. Freq.: 12.4 GHz Booting: SMA Jack Straight I			Contact Material:	Beryllium Copper	
Max. Freq.: 12.4 GHz Booting: SMA Jack Straight			Contact Finish:	Gold	
Booting: SMA Jack Straight			Max. Freq.:	6 GHz	
	RP		Booting:	HD-BNC Jack Straig	ht BHD
	-		Clocking:	0°	
	THIS DRAWING MAY CONTAIN PATENTED OR	Title:			UNLESS SPECIFIED
	PROPRIETARY INFORMATION AND MUST NOT BE U: FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CAE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBE IN ANY FORM WITHOUT THE WRITTEN CONSENT O	LE D	NC-ST-JK G316 481		TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY:
CONTROLLED DOCUMENT DO NOT CORV	CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWII ESTABLISHES AND AGREEMENT OF THE FOREGOIN	NG Part No:	Part No: CENTER LABEL		CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES



## **RoHS 2015/863 Compliance Statement**

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/1/2023

Part Number: Q-7100P0005048I

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-JK-RP/HDBNC-ST-JK G316 48I

This information is valid as of the date indicated for the item (part number) listed.

**Director of Quality Assurance** 

Janice Frank