


| NO. | PART NAME | MATERIAL | PLATING | REMARKS |
|-----|-------------------------|-----------|------------|------------|
| 1 | HOUSING | POLYAMIDE | | UL94V0 |
| 2 | BOTTOM COVER | POLYAMIDE | | UL94V0 |
| 3 | RING TERMINAL | Cu-Ti | GOLD FLASH | 25 MICRONS |
| 4 | TIP TERMINAL | Cu-Ti | GOLD FLASH | 25 MICRONS |
| 5 | SLEEVE (EARTH) TERMINAL | PBS | GOLD FLASH | 30 MICRONS |

SPECIFICATIONS:

1. RATED VOLTAGE-16 VDC
2. RATED CURRENT-300 mA
3. CONTACT RESISTANCE-100 MOHMS OR LESS UNDER ALL CONDITIONS, INCLUDING AFTER LIFE TESTING.
4. INSULATION RESISTANCE-100 MOHMS OR GREATER AT 500 VDC.
5. DIELECTRIC WITHSTAND VOLTAGE-500 VAC RMS FOR 1 MINUTE.



9815 SW Allen, Suite 109
 Beaverton, OR 97005
 Phone: (503) 643-4899
 800-275-4899
 Fax: (503) 372-1286
 Website: www.cui.com

TITLE: 3.5mm SURFACE MOUNT AUDIO JACK-STEREO
 PART NO.: SJ-3513-SMT
 UNITS: Millimeters
 DRAWN BY: Todd R. White
 APPROVED BY:
 SCALE: 3X