



Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > Ribbon Cable Connectors >

Crimp-on-Snap-in Housing



Connector System: **Wire-to-Board**

Number of Positions: **14**

Centerline (Pitch): **1.27 mm [.05 in]**

Row-to-Row Spacing: **2 mm [.059 in]**

Number of Rows: **2**

[All Crimp-on-Snap-in Housing \(9\)](#)

Features

Product Type Features

Ribbon Cable Connector Header Type	Shrouded
Connector Product Type	Housing
Connector System	Wire-to-Board
Connector & Housing Type	Plug
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	14
Number of Rows	2

Electrical Characteristics

Insulation Resistance	1000 MΩ
Operating Voltage	100 VAC

Body Features

Daisy Chain	Without
Primary Product Color	Red
Connector Profile	Standard

Contact Features

--	--



Contact Type	Socket
Contact Mating Area Plating Material	Tin
PCB Contact Termination Area Plating Material Finish	Matte
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	1.5 A

Termination Features

Termination Method to Wire & Cable	Crimp & Snap
------------------------------------	--------------

Mechanical Attachment

Mating Alignment	With
Contact Retention Type Within Housing	Snap-In
PCB Mount Alignment	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Retention Type	Contact Friction

Housing Features

Housing Material	PBT GF
Centerline (Pitch)	1.27 mm[.05 in]

Dimensions

Connector Length	21.1 mm[.83 in]
Connector Height	12.4 mm[.49 in]
PCB Thickness (Recommended)	1.6 mm[.06 in]
Row-to-Row Spacing	2 mm[.059 in]

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

UL Rating	Recognized
Agency/Standard	UL
Approved Standards	UL E28476



UL Flammability Rating

UL 94V-0

Packaging Features

Packaging Quantity	350
Packaging Method	Box & Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-M5833-F3492A
Female-on-Board Connector, Top Entry



TE Part # CAT-M5833-C8684A
Crimp Contacts - Micro-MaTch Entry



TE Part # 8-215460-4
MICR-MATCH FSID P




TE Part # 1-338070-4
MICRO-MATCH FEM.SE



TE Part # 8-188431-4
M-MATCH FEM. BOTTOM ENTRY
SMD INB.CONN.



TE Part # 734870-2
CRIMP HT, MICRO-MATCH COSI, AW



TE Part # 1-215460-4
MICRO-MATCH FEM.SE



TE Part # 734870-1
CRIMP HT, MICRO-MATCH COSI, AW



TE Part # 1-100400-4
MICRO-MATCH FSID NP




TE Part # 5-1579008-3
EXTRACTION TOOL



TE Part # 8-100400-4
MICRO-MATCH FSID NP


Also in the Series | Micro-MaTch Industrial



Board-In Connectors(20)



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(1)



Pluggable I/O Cable Assemblies(52)



Ribbon Cable Connectors(185)



Wire-to-Board Connector Contacts(4)

Customers Also Bought



TE Part #W2SC
WEDGE LOCK, 2P, PLG, GRN, STD,
DT, C



TE Part #3-647166-6
6P MTA100 HDR ASSY,SM,FL,LF



TE Part #4-1614884-3
CPF 0805 120R 0.1% 25PPM 1K RL



TE Part #1011-229-0205
BKSHL, 2P, BLK, REC, ST, NW6/7.5/8.5
/10



TE Part #338096-1
MICRO-MATCH COSICNT



TE Part #1060-16-0144
PIN, SF, SIZE 16, 14-18, AU/SN



TE Part #1718760-1
MCON 1.2 LL TAB SWS SN



TE Part #1-1703498-3
2POS, MCON 1.2 LL TAB SEALED
COD A



TE Part #4-2600021-5
XRC SOCKET 16-20 AWG Gold Plated

Documents

Product Drawings

MICRO-MATCH COSI HSG

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-338095-4_D_c-1-338095-4-d.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-338095-4_D_c-1-338095-4-d.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-338095-4_D_c-1-338095-4-d.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Micro-MaTch Catalog

English

Centerline Micro-Match Connector Series

English

Product Specifications

micro-match crimp on snap in male on wire connector

English



Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English