

DC/DC converter

Input 9-36 and 18-72 Vdc

Output up to 0.5 A / 3 W

Key Features

- *Industry standard DIL24*
- *Wide input voltage range, 9–36 V, 18–72 V*
- *High efficiency 74–83% typical*
- *Low idling power*
- *Full output power up to +75 °C ambient temperature*
- *Input/Output isolation 1,500 Vdc*
- *MTBF > 650,000 hours at +25°C ambient*
- *Basic insulation according to UL 62368-1*

Safety Approvals



Design for Environment



Meets requirements in high-temperature lead-free soldering processes.

The PKV series of DC/DC power modules is intended for general use in 12/24V and 48/60V DC systems. Designed with MOSFET transistors and 200 kHz switching frequency, they are characterized by high efficiency over a wide load range, very low quiescent power and an excellent line and load regulation.

The DC/DC power modules are encapsulated in an epoxy filled plastic box. The flammability ratings of the en

capsulating materials are in conformance with UL 94V-0 and have an adequate thermal conductivity. The materials withstand all normal PBA cleaning methods. Flex is an ISO 9001/14001 certified supplier.

General

Absolute Maximum Ratings

Characteristics		min	max	Units
T _c	Case temperature ¹⁾	-40	+95	°C
T _s	Storage temperature	-40	+125	°C
V _i	Input voltage, 0.1 s max	PKV 3000 PKV 5000	40 80	Vdc
V _{iso}	Isolation voltage ²⁾ (input to output test voltage)		1,500	Vdc

Stress in excess of Absolute Maximum Ratings may cause permanent damage. Absolute Maximum Ratings, sometimes referred to as no destruction limits, are normally tested with one parameter at a time exceeding the limits of Output data or Electrical Characteristics. If exposed to stress above these limits, function and performance may degrade in an unspecified manner.

Note:

- 1) Corresponding typical ambient temperature range (T_A) at full output power is -40 to +75°C.
- 2) Typical Isolation voltage of PKV5211 module is 2,000 Vdc

Input T_A = +25°C, unless otherwise specified

Characteristics		Conditions	min	typ	max	Units
V _i	Input voltage range	T _A = -40 to +75°C	PKV 3000 PKV 5000	9 18	36 72	V
V _{loff}	Turn-off input voltage		PKV 3000 PKV 5000		8 16	V
	Inrush current Peak I _{2t}	Low loss, low inductive capacitive source	PKV 3000 PKV 5000	35 0.005 0.005	A A ² s A ² s	
	Idling power	I _o = 0			0.3	W
V _{iac}	Ripple voltage	I _o = I _{omax} , BW=20 MHz		100		mV _{p-p}

Miscellaneous

Characteristics		Conditions	min	typ	max	Unit
	Input/Output coupling capacitor	RH = 48%, T _c = +25°C f = 100 Hz		1000		pF
	Switching frequency	V _i = V _{inom} , I _o = I _{omax}		200		kHz

Environmental Characteristics

Test method	Reference	Test procedure & conditions		
Vibration (Sinusoidal)	IEC 68-2-6 F _C	Frequency Amplitude Acceleration Number of cycles Test duration	10...500Hz 0.75 mm 10 g 10 in each axis 1 h per axis	
Shock (Half-sinus)	IEC 68-2-27 E _a	Peak acceleration Shock duration	200g 3 ms	
Temperature change	IEC 68-2-14 N _a	Temperature Number of cycles	-40°C to +125°C 100	

Safety

The PKV 3000 I and PKV 5000 I series DC/DC converters are designed in accordance with safety standards UL 62368-1, *Safety of Information Technology Equipment*. The PKV 3000 I and PKV 5000 I series DC/DC converters are UL 62368-1 recognized. The DC/DC converter should be installed in the end-use equipment, in accordance with the requirements of the ultimate application. The input source must be isolated by minimum Basic insulation from the primary circuit in accordance with UL 62368-1. If the input voltage to the DC/DC converter is 72 V dc or less, then the output remains SELV (Safety Extra Low Voltage) under normal and abnormal operating conditions.


It is recommended that a slow blow fuse with a rating of 2 x I_{max} be used at the input of each DC/DC converter. If a fault occurs in the converter that imposes a short circuit on the input source, this fuse will provide the following functions:

- Isolate the faulty DC/DC converter from the input power source not to affect the operation of other parts of the system.
- Protect the distribution wiring from excessive current and power loss thus preventing hazardous overheating.

The galvanic isolation is verified in an electric strength test. The test voltage (V_{iso}) between input and output is 1500 Vdc for 60 seconds. Leakage current is less than 1µA at nominal input voltage.

The flammability rating for all construction parts of the DC/DC converter meets UL 94V-0.

Mechanical Data



Connections

Pin	Designation	Function	
		Single output	Dual output
2	-In	Negative input	Negative input
3	-In	Negative input	Negative input
9	NC/Rtn	Not connected	Output return
10	NC	Not connected	Not connected
11	NC/-Out	Not connected	Negative output
14	+Out	Positive output	Positive output
15	NC	Not connected	Not connected
16	Rtn	Output return	Output return
22	+In	Positive input	Positive input
23	+In	Positive input	Positive input

Weight:

Maximum 15 g
(0.53 oz).

Pins:

Material: Copper
Plating: 3 μ m Tin over 1.5 μ m Ni

Case:

Non-conductive plastic, UL 94V-0.

PKV 3211 PI


Output

$T_A = +25^\circ\text{C}$, $V_I = 9 \dots 36 \text{ V}$ unless otherwise specified.

Characteristics	Conditions	Output 1			Unit
		min	typ	max	
V_O	Output voltage tolerance band	$I_O = 0.1 \dots 1.0 \times I_{O\max}$ and long term drift	4.90	5.10	V
	Line regulation	$I_O = I_{O\max}$	10	25	mV
	Load regulation	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 26 \text{ V}$	10	50	mV
t_{tr}	Load transient recovery time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 26 \text{ V}$ load step = $0.5 \times I_{O\max}$	300		μs
V_{tr}	Load transient voltage		+100		mV
			-100		mV
T_{coeff}	Temperature coefficient	Measured after stabilization			$^\circ\text{C}$
t_r	Ramp-up time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$	0.5		ms
t_s	Start-up time	$V_I = 26 \text{ V}$	800	1300	ms
I_O	Output current				A
$P_{O\max}$	Max output power				W
I_{lim}	Current limiting threshold ¹⁾	$T_C < T_{C\max}$	0.5	1.62	A
I_{sc}	Short circuit current	$V_I = 26 \text{ V}$	0.25		A
$V_{O\text{ ac}}$	Output ripple & noise	$I_O = I_{O\max}$, $T_A = 25^\circ\text{C}$	60		mV _{p-p}
SVR	Supply voltage rejection (ac)	$f = 100/120 \text{ Hz sine wave, } 1 \text{ V}_{p-p}, (SVR = 20 \log (1 \text{ V}_{p-p}/V_{O\text{ p-p}}))$			dB

1) At $V_{out} \leq 80\%$ of nominal the power module goes into hick up mode.

Miscellaneous



Characteristics	Conditions	min	typ	max	Unit
η	Efficiency	$I_O = I_{O\max}$, $V_I = 26 \text{ V}$	76	82	%
P_d	Power dissipation	$I_O = I_{O\max}$, $V_I = 26 \text{ V}$	0.55	0.79	W

PKV 3313 PI


Output

$T_A = +25^\circ\text{C}$, $V_I = 9 \dots 36 \text{ V}$ unless otherwise specified.

Characteristics	Conditions	Output 1			Unit
		min	typ	max	
V_O	Output voltage tolerance band	$I_O = 0.1 \dots 1.0 \times I_{O\max}$ and long term drift	11.76	12.24	V
	Line regulation	$I_O = I_{O\max}$	24	60	mV
	Load regulation	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 26 \text{ V}$	24	120	mV
t_{tr}	Load transient recovery time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 26 \text{ V}$ load step = $0.5 \times I_{O\max}$	300		μs
V_{tr}	Load transient voltage		+150		mV
			-150		mV
T_{coeff}	Temperature coefficient	Measured after stabilization		± 0.02	$^\circ\text{C}$
t_r	Ramp-up time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 26 \text{ V}$	1.2		ms
t_s	Start-up time	From V_I connection to $V_O = 0.9 \times V_{Oi}$	800	1300	ms
I_O	Output current			0.25	A
$P_O \max$	Max output power		3		W
I_{lim}	Current limiting threshold ¹⁾	$T_C < T_{C\max}$	0.25	0.81	A
I_{sc}	Short circuit current	$V_I = 26 \text{ V}$	0.35		A
$V_O \text{ ac}$	Output ripple & noise	$I_O = I_{O\max}$, $T_A = 25^\circ\text{C}$	DC ... 20 MHz	60	$\text{mV}_{\text{p-p}}$
SVR	Supply voltage rejection (ac)	$f = 100/120 \text{ Hz sine wave, } 1 \text{ V}_{\text{p-p}}$, ($\text{SVR} = 20 \log (1 \text{ V}_{\text{p-p}}/V_{O\text{p-p}})$)		60	dB

1) At $V_{out} \leq 80\%$ of nominal the power module goes into hick up mode.

Miscellaneous



Characteristics		Conditions	min	typ	max	Unit
η	Efficiency	$I_O = I_{O\max}$, $V_I = 26 \text{ V}$	76	82		%
P_d	Power dissipation	$I_O = I_{O\max}$, $V_I = 26 \text{ V}$		0.66	0.95	W

PKV 3315 PI


Output

$T_A = +25^\circ\text{C}$, $V_I = 9 \dots 36 \text{ V}$ unless otherwise specified.

Characteristics	Conditions	Output 1			Unit
		min	typ	max	
V_O	Output voltage tolerance band	$I_O = 0.1 \dots 1.0 \times I_{O\max}$ and long term drift	14.7	15.3	V
	Line regulation	$I_O = I_{O\max}$	30	75	mV
	Load regulation	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 26 \text{ V}$	30	150	mV
t_{tr}	Load transient recovery time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 26 \text{ V}$ load step = $0.5 \times I_{O\max}$	300		μs
V_{tr}	Load transient voltage		+200		mV
			-200		mV
T_{coeff}	Temperature coefficient	Measured after stabilization			$\pm 0.02 \text{ } ^\circ\text{C}^{-1}$
t_r	Ramp-up time	$I_O = 0.1 \dots 0.9 \times V_O$	1.2		ms
t_s	Start-up time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 26 \text{ V}$	800	1300	ms
I_O	Output current				0.2 A
$P_O \max$	Max output power				W
I_{lim}	Current limiting threshold ¹⁾	$T_C < T_{C\max}$	0.2	0.65	A
I_{sc}	Short circuit current	$V_I = 26 \text{ V}$	0.35		A
$V_O \text{ ac}$	Output ripple & noise	$I_O = I_{O\max}$, $T_A = 25^\circ\text{C}$	60		mV _{p-p}
SVR	Supply voltage rejection (ac)	$f = 100/120 \text{ Hz sine wave, } 1 \text{ V}_p{}_p$, ($\text{SVR} = 20 \log (1 \text{ V}_p{}_p / V_{O\text{p-p}})$)			dB

¹⁾ At $V_{out} \leq 80\%$ of nominal the power module goes into hick up mode.

Miscellaneous



Characteristics	Conditions	min	typ	max	Unit
η	Efficiency	$I_O = I_{O\max}$, $V_I = 26 \text{ V}$	76	82	%
P_d	Power dissipation	$I_O = I_{O\max}$, $V_I = 26 \text{ V}$	0.66	0.95	W

PKV 3222 PI


Output

$T_A = +25^\circ\text{C}$, $V_i = 9 \dots 36\text{V}$ unless otherwise specified.

Characteristics	Conditions	Output 1			Output 2			Unit
		min	typ	max	min	typ	max	
V_o	Output voltage tolerance band	$I_o = 0.1 \dots 1.0 \times I_{o\max}$ and long term drift	+4.9	+5.1	-4.9	-5.1	-	V
	Line regulation	$I_o = I_{o\max}$	10	25	10	25	mV	
	Load regulation	$I_o = 0.1 \dots 1.0 \times I_{o\max}$, $V_i = 26\text{ V}$	10	50	10	50	mV	
t_{tr}	Load transient recovery time	$I_o = 0.1 \dots 1.0 \times I_{o\max}$, $V_i = 26\text{ V}$ load step = $0.5 \times I_{o\max}$	300		300		μs	
V_{tr}	Load transient voltage		+100		+100		mV	
			-100		-100		mV	
T_{coeff}	Temperature coefficient	Measured after stabilization			±0.02		±0.02	%/°C
t_r	Ramp-up time	$I_o = 0.1 \dots 1.0 \times I_{o\max}$, $V_i = 26\text{ V}$	0.1 ... 0.9 × V_o	1.2	1.2		ms	
t_s	Start-up time		From V_i connection to $V_o = 0.9 \times V_{oi}$	800	1300	800	1300	ms
I_o	Output current			0.25		0.25	A	
$P_{o\max}$	Max output power			1.25	1.25		W	
I_{lim}	Current limiting threshold ¹⁾	$T_c < T_{c\max}$			0.25	0.81	0.25	A
I_{sc}	Short circuit current	$V_i = 26\text{ V}$			0.25	0.25	A	
$V_{o\ ac}$	Output ripple & noise	$I_o = I_{o\max}$, $T_A = 25^\circ\text{C}$	DC ... 20 MHz	60	60		mV _{p-p}	
SVR	Supply voltage rejection (ac)	$f = 100/120\text{ Hz sine wave, } 1\text{ V}_p{}_p$, $(\text{SVR} = 20 \log (1\text{ V}_p{}_p/V_{o\ p-p}))$			45	45		dB

1) At $V_{out} \leq 80\%$ of nominal the power module goes into hick up mode.

Miscellaneous



Characteristics		Conditions	min	typ	max	Unit
η	Efficiency	$I_o = I_{o\max}$, $V_i = 26\text{ V}$	75	82		%
P_d	Power dissipation	$I_o = I_{o\max}$, $V_i = 26\text{ V}$		0.55	0.83	W

PKV 3321 PI


Output

$T_A = +25^\circ\text{C}$, $V_I = 9 \dots 36\text{V}$ unless otherwise specified.

Characteristics	Conditions	Output 1			Output 2			Unit
		min	typ	max	min	typ	max	
V_O	Output voltage tolerance band	$I_O = 0.1 \dots 1.0 \times I_{O\max}$ and long term drift	+11.76	+12.24	-11.76	-12.24	-	V
	Line regulation	$I_O = I_{O\max}$	24	60	24	60	mV	
	Load regulation	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 26\text{ V}$	24	120	24	120	mV	
t_{tr}	Load transient recovery time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 26\text{ V}$ load step = $0.5 \times I_{O\max}$	300		300		μs	
V_{tr}	Load transient voltage		+150		+150		mV	
			-150		-150		mV	
T_{coeff}	Temperature coefficient	Measured after stabilization			±0.02		±0.02	%/°C
t_r	Ramp-up time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$	1.2		1.2		ms	
t_s	Start-up time	$V_I = 26\text{ V}$	800	1300	800	1300	ms	
I_O	Output current				0.125		0.125	A
$P_{O\max}$	Max output power				1.5		1.5	W
I_{lim}	Current limiting threshold ¹⁾	$T_C < T_{C\max}$	0.125	0.400	0.125	0.400	A	
I_{sc}	Short circuit current	$V_I = 26\text{ V}$	0.35		0.35		A	
$V_{O\text{ ac}}$	Output ripple & noise	$I_O = I_{O\max}$, $T_A = 25^\circ\text{C}$	DC ... 20 MHz	60		60	mV _{p-p}	
SVR	Supply voltage rejection (ac)	$f = 100/120\text{ Hz sine wave, } 1\text{ V}_{p-p}$, ($\text{SVR} = 20 \log (1\text{ V}_{p-p}/V_{O\text{ p-p}})$)			45		45	dB

1) At $V_{out} \leq 80\%$ of nominal the power module goes into hick up mode.

Miscellaneous



Characteristics		Conditions	min	typ	max	Unit
η	Efficiency	$I_O = I_{O\max}$, $V_I = 26\text{ V}$	73	82		%
P_d	Power dissipation	$I_O = I_{O\max}$, $V_I = 26\text{ V}$		0.66	1.11	W

PKV 3325 PI


Output

$T_A = +25^\circ\text{C}$, $V_i = 9\ldots36\text{V}$ unless otherwise specified.

Characteristics		Conditions	Output 1			Output 2			Unit	
			min	typ	max	min	typ	max		
V_o	Output voltage tolerance band	$I_o = 0.1 \ldots 1.0 \times I_{o\max}$ and long term drift	+14.7	+15.3	-14.7	-15.3	-	-	V	
	Line regulation	$I_o = I_{o\max}$	30	75	30	75	30	75	mV	
	Load regulation	$I_o = 0.1 \ldots 1.0 \times I_{o\max}$, $V_i = 26\text{ V}$	30	150	30	150	30	150	mV	
t_{tr}	Load transient recovery time	$I_o = 0.1 \ldots 1.0 \times I_{o\max}$, $V_i = 26\text{ V}$ load step = $0.5 \times I_{o\max}$	300	300	300	300	300	300	μs	
V_{tr}	Load transient voltage		+200	+200	+200	+200	+200	+200	mV	
T_{coeff}	Temperature coefficient		-200	-200	-200	-200	-200	-200	mV	
	Measured after stabilization	-	-	-	-	-	-	%/ $^\circ\text{C}$		
t_r	Ramp-up time	$I_o = 0.1 \ldots 0.9 \times V_o$	1.2	1.2	1.2	1.2	1.2	1.2	ms	
t_s	Start-up time	$I_o = 0.1 \ldots 1.0 \times I_{o\max}$, $V_i = 26\text{ V}$	From V_i connection to $V_o = 0.9 \times V_{oi}$	800	1300	800	1300	800	1300	ms
I_o	Output current				0.1	0.1	0.1	0.1	A	
$P_{o\max}$	Max output power				1.5	1.5	1.5	1.5	W	
I_{lim}	Current limiting threshold ¹⁾	$T_C < T_{C\max}$	0.10	0.32	0.10	0.32	0.10	0.32	A	
I_{sc}	Short circuit current	$V_i = 26\text{ V}$	0.35	0.35	0.35	0.35	0.35	0.35	A	
$V_{o\text{ ac}}$	Output ripple & noise	$I_o = I_{o\max}$, $T_A = 25^\circ\text{C}$	DC ... 20 MHz	50	50	50	50	50	mV _{p-p}	
SVR	Supply voltage rejection (ac)	$f = 100/120\text{ Hz sine wave, } 1\text{ V}_p{}_p$, ($\text{SVR} = 20 \log (1\text{ V}_p{}_p/V_{op-p})$)			45	45	45	45	dB	

1) At $V_{out} \leq 80\%$ of nominal the power module goes into hick up mode.

Miscellaneous



Characteristics		Conditions	min	typ	max	Unit
η	Efficiency	$I_o = I_{o\max}$, $V_i = 26\text{ V}$	76	80	-	%
P_d	Power dissipation	$I_o = I_{o\max}$, $V_i = 26\text{ V}$	-	0.75	0.95	W

PKV 5211 PI


Output

$T_A = +25^\circ\text{C}$, $V_I = 18 \dots 72\text{V}$ unless otherwise specified. Maximum Recommended Capacitive Load = $660\mu\text{F}$.

Characteristics		Conditions	Output 1			Unit
			min	typ	max	
V_O	Output voltage tolerance band	$I_O = 0.1 \dots 1.0 \times I_{O\max}$ and long term drift	4.90	5.10	5.10	V
	Line regulation	$I_O = I_{O\max}$		10	25	mV
	Load regulation	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 53\text{ V}$		10	50	mV
t_{tr}	Load transient recovery time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 53\text{ V}$ load step = $0.5 \times I_{O\max}$		300		μs
V_{tr}	Load transient voltage			+100		mV
				-100		mV
T_{coeff}	Temperature coefficient	Measured after stabilization			± 0.02	$^\circ\text{C}$
t_r	Ramp-up time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 53\text{ V}$		0.5		ms
t_s	Start-up time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 53\text{ V}$	From V_I connection to $V_O = 0.9 \times V_{O_i}$	900	1300	ms
I_O	Output current				0.5	A
$P_{O\max}$	Max output power			2.5		W
I_{lim}	Current limiting threshold ¹⁾	$T_C < T_{C\max}$		0.5	1.62	A
I_{sc}	Short circuit current	$V_I = 53\text{ V}$		0.12		A
$V_O \text{ ac}$	Output ripple & noise	$I_O = I_{O\max}$, $T_A = 25^\circ\text{C}$	DC ... 20 MHz	60		$\text{mV}_{\text{p-p}}$
SVR	Supply voltage rejection (ac)	$f = 100/120\text{ Hz sine wave, } 1\text{ V}_{\text{p-p}}$, $(\text{SVR} = 20 \log (1\text{ V}_{\text{p-p}}/V_{O\text{p-p}}))$		60		dB

1) At $V_{out} \leq 80\%$ of nominal the power module goes into hick up mode.

Miscellaneous



Characteristics		Conditions	min	typ	max	Unit
η	Efficiency	$I_O = I_{O\max}$, $V_I = 53\text{ V}$	75	82		%
P_d	Power dissipation	$I_O = I_{O\max}$, $V_I = 53\text{ V}$		0.55	0.84	W

PKV 5315 PI


Output

$T_A = +25^\circ\text{C}$, $V_I = 18\ldots72\text{V}$ unless otherwise specified.

Characteristics	Conditions	Output 1			Unit
		min	typ	max	
V_O	Output voltage tolerance band	$I_O = 0.1 \ldots 1.0 \times I_{O\max}$ and long term drift	14.7	15.3	V
	Line regulation	$I_O = I_{O\max}$	30	75	mV
	Load regulation	$I_O = 0.1 \ldots 1.0 \times I_{O\max}$, $V_I = 53\text{ V}$	30	150	mV
t_{tr}	Load transient recovery time	$I_O = 0.1 \ldots 1.0 \times I_{O\max}$, $V_I = 53\text{ V}$ load step = $0.5 \times I_{O\max}$	300		μs
V_{tr}	Load transient voltage		+200		mV
			-200		mV
T_{coeff}	Temperature coefficient	Measured after stabilization		± 0.02	$^\circ/\text{C}$
t_r	Ramp-up time	$I_O = 0.1 \ldots 1.0 \times I_{O\max}$	1.2		ms
t_s	Start-up time	$V_I = 53\text{ V}$	900	1300	ms
I_O	Output current			0.2	A
$P_O \max$	Max output power		3		W
I_{lim}	Current limiting threshold ¹⁾	$T_c < T_{c\max}$	0.20	0.65	A
I_{sc}	Short circuit current	$V_I = 53\text{ V}$	0.17		A
$V_O \text{ ac}$	Output ripple & noise	$I_O = I_{O\max}$, $T_A = 25^\circ\text{C}$	60		$\text{mV}_{\text{p-p}}$
SVR	Supply voltage rejection (ac)	$f = 100/120\text{ Hz sine wave}$, $1\text{ V}_{\text{p-p}}$, ($\text{SVR} = 20 \log (1\text{ V}_{\text{p-p}}/V_{O\text{p-p}})$)	60		dB

1) At $V_{out} \leq 80\%$ of nominal the power module goes into hick up mode.

Miscellaneous



Characteristics		Conditions	min	typ	max	Unit
η	Efficiency	$I_O = I_{O\max}$, $V_I = 53\text{ V}$	76	82		%
P_d	Power dissipation	$I_O = I_{O\max}$, $V_I = 53\text{ V}$		0.66	0.95	W

PKV 5222 PI


Output

$T_A = +25^\circ\text{C}$, $V_I = 18 \dots 72\text{V}$ unless otherwise specified.

Characteristics	Conditions	Output 1			Output 2			Unit
		min	typ	max	min	typ	max	
V_O	Output voltage tolerance band	$I_O = 0.1 \dots 1.0 \times I_{O\max}$ and long term drift	+4.9	+5.1	-4.9	-5.1	-5.1	V
	Line regulation	$I_O = I_{O\max}$	10	25	10	25	25	mV
	Load regulation	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 53\text{V}$	10	50	10	50	50	mV
t_{tr}	Load transient recovery time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 53\text{V}$ load step = $0.5 \times I_{O\max}$	300		300			μs
V_{tr}	Load transient voltage		+100		+100			mV
			-100		-100			mV
T_{coeff}	Temperature coefficient	Measured after stabilization		+0.02		+0.02		%/°C
t_r	Ramp-up time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$	1.2		1.2			ms
t_s	Start-up time	$V_I = 53\text{V}$	From V_I connection to $V_O = 0.9 \times V_{OI}$	900	1300	900	1300	ms
I_O	Output current			0.25		0.25		A
$P_{O\max}$	Max output power			1.25		1.25		W
I_{lim}	Current limiting threshold ¹⁾	$T_C < T_{C\max}$		0.25	0.81	0.25	0.81	A
I_{sc}	Short circuit current	$V_I = 53\text{V}$		0.12		0.12		A
$V_{O\text{ ac}}$	Output ripple & noise	$I_O = I_{O\max}$, $T_A = 25^\circ\text{C}$	DC ... 20 MHz	60		60		mV _{p-p}
SVR	Supply voltage rejection (ac)	$f = 100/120\text{ Hz sine wave, } 1\text{ V}_{p-p}$, $(\text{SVR} = 20 \log (1\text{ V}_{p-p}/V_{O\text{ p-p}}))$		45		45		dB

1) At $V_{out} \leq 80\%$ of nominal the power module goes into hick up mode.

Miscellaneous



Characteristics		Conditions	min	typ	max	Unit
η	Efficiency	$I_O = I_{O\max}$, $V_I = 53\text{V}$	75	82		%
P_d	Power dissipation	$I_O = I_{O\max}$, $V_I = 53\text{V}$		0.55	0.83	W

PKV 5321 PI


Output

$T_A = +25^\circ\text{C}$, $V_i = 18 \dots 72\text{V}$ unless otherwise specified.

Characteristics		Conditions	Output 1			Output 2			Unit
			min	typ	max	min	typ	max	
V_o	Output voltage tolerance band	$I_o = 0.1 \dots 1.0 \times I_{o\max}$ and long term drift	+11.76	+12.24	-11.76	-12.24	-	-	V
	Line regulation	$I_o = I_{o\max}$	24	60	24	60	24	60	mV
	Load regulation	$I_o = 0.1 \dots 1.0 \times I_{o\max}$, $V_i = 53\text{ V}$	24	120	24	120	24	120	mV
t_{tr}	Load transient recovery time	$I_o = 0.1 \dots 1.0 \times I_{o\max}$, $V_i = 53\text{ V}$ load step = $0.5 \times I_{o\max}$	300	300	300	300	300	300	μs
V_{tr}	Load transient voltage		+150	+150	+150	+150	+150	+150	mV
			-150	-150	-150	-150	-150	-150	mV
T_{coeff}	Temperature coefficient	Measured after stabilization	-	-	± 0.02	-	-	± 0.02	$^\circ\text{C}$
t_r	Ramp-up time	$I_o = 0.1 \dots 1.0 \times I_{o\max}$, $V_i = 53\text{ V}$	1.2	1.2	1.2	1.2	1.2	1.2	ms
t_s	Start-up time	From V_i connection to $V_o = 0.9 \times V_{oi}$	900	1300	900	1300	900	1300	ms
I_o	Output current	-	-	0.125	-	-	0.125	0.125	A
$P_{o\max}$	Max output power	-	-	1.5	-	-	1.5	1.5	W
I_{lim}	Current limiting threshold ¹⁾	$T_c < T_{c\max}$	0.125	0.400	0.125	0.400	0.125	0.400	A
I_{sc}	Short circuit current	$V_i = 53\text{ V}$	0.17	0.17	0.17	0.17	0.17	0.17	A
$V_{o\text{ ac}}$	Output ripple & noise	$I_o = I_{o\max}$, $T_A = 25^\circ\text{C}$	DC ... 20 MHz	60	60	60	60	60	$\text{mV}_{\text{p-p}}$
SVR	Supply voltage rejection (ac)	$f = 100/120\text{ Hz sine wave, } 1\text{ V}_{\text{p-p}}$, $(\text{SVR} = 20 \log (1\text{ V}_{\text{p-p}}/V_{Op-p}))$	-	45	-	-	45	45	dB

1) At $V_{out} \leq 80\%$ of nominal the power module goes into hick up mode.

Miscellaneous



Characteristics		Conditions	min	typ	max	Unit
η	Efficiency	$I_o = I_{o\max}$, $V_i = 53\text{ V}$	73	82	-	%
P_d	Power dissipation	$I_o = I_{o\max}$, $V_i = 53\text{ V}$	-	0.66	1.11	W

PKV 5325 PI


Output

$T_A = +25^\circ\text{C}$, $V_I = 18 \dots 72\text{V}$ unless otherwise specified.

Characteristics	Conditions	Output 1			Output 2			Unit
		min	typ	max	min	typ	max	
V_O	Output voltage tolerance band	$I_O = 0.1 \dots 1.0 \times I_{O\max}$ and long term drift	+14.7	+15.3	-14.7	-15.3	-15.3	V
	Line regulation	$I_O = I_{O\max}$	30	75	30	75	75	mV
	Load regulation	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 53\text{ V}$	30	150	30	150	150	mV
t_{tr}	Load transient recovery time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 53\text{ V}$ load step = $0.5 \times I_{O\max}$	300		300		300	μs
V_{tr}	Load transient voltage		+200		+200		+200	mV
			-200		-200		-200	mV
T_{coeff}	Temperature coefficient	Measured after stabilization		+0.02		+0.02		%/ $^\circ\text{C}$
t_r	Ramp-up time	$I_O = 0.1 \dots 0.9 \times V_O$	1.2		1.2		1.2	ms
t_s	Start-up time	$I_O = 0.1 \dots 1.0 \times I_{O\max}$, $V_I = 53\text{ V}$	From V_I connection to $V_O = 0.9 \times V_O$	900	1300	900	1300	ms
I_O	Output current			0.1		0.1	0.1	A
$P_{O\max}$	Max output power			1.5		1.5		W
I_{lim}	Current limiting threshold ¹⁾	$T_C < T_{C\max}$		0.10	0.32	0.10	0.32	A
I_{sc}	Short circuit current	$V_I = 53\text{ V}$		0.17		0.17	0.17	A
$V_{O\text{ ac}}$	Output ripple & noise	$I_O = I_{O\max}$, $T_A = 25^\circ\text{C}$	DC ... 20 MHz	60		60		mV _{p-p}
SVR	Supply voltage rejection (ac)	$f = 100/120\text{ Hz sine wave, } 1\text{ V}_{p-p}$, $(\text{SVR} = 20 \log (1\text{ V}_{p-p}/V_{O\text{ p-p}}))$		45		45		dB

1) At $V_{out} \leq 80\%$ of nominal the power module goes into hick up mode.

Miscellaneous



Characteristics	Conditions	min	typ	max	Unit
η	$I_O = I_{O\max}$, $V_I = 53\text{ V}$	76	82		%
P_d	$I_O = I_{O\max}$, $V_I = 53\text{ V}$		0.66	0.95	W

EMC Specifications

The PKV DC/DC power module is mounted on a double sided printed circuit board (PB) with groundplane during EMC measurements. The fundamental switching frequency is approx. 200 kHz.

The PKV series has a good input filter and will only need a simple filter to meet conducted noise according to EN 55022 level B. Fig. 1 shows an example of filter and the results for this filter is shown below.






Fig. 1


Conducted noise




PKV 3211 without filter




PKV 3211 with filter



PKV 5211 without filter



PKV 5211 with filter



Miscellaneous

Soldering Information

The PKV Series DC/DC Converters are intended for through hole mounting in a PCB. When wave soldering is used, the temperature on the pins is specified to maximum 260 °C for maximum 10 seconds. Maximum preheat rate of 4 °C/s and temperature of max 150 °C is suggested. When hand soldering, care should be taken to avoid direct contact between the hot soldering iron tip and the pins for more than a few seconds in order to prevent overheating.

A no-clean (NC) flux is recommended to avoid entrapment of cleaning fluids in cavities inside of the DC/DC power module. The residues may affect long time reliability and isolation voltage.

External Decoupling Capacitors

When powering loads with significant dynamic current requirements, the voltage regulation at the point of load can be improved by addition of decoupling capacitors at the load. The most effective technique is to locate low ESR ceramic and electrolytic capacitors as close to the load as possible, using several parallel capacitors to lower the effective ESR. The ceramic capacitors will handle high-frequency dynamic load changes while the electrolytic capacitors are used to handle low frequency dynamic load changes. Ceramic capacitors will also reduce any high frequency noise at the load. It is equally important to use low resistance and low inductance PCB layouts and cabling.

External decoupling capacitors will become part of the control loop of the DC/DC converter and may affect the stability margins. As a "rule of thumb", 100 μF/A of output current can be added without any additional analysis. The ESR of the capacitors is a very important parameter. Power Modules guarantee stable operation with a verified ESR value of > 10 mOhm across the output connections.

For further information please contact your local Flex representative.

Delivery Package Information

The PKV series DC/DC converters are delivered in tubes with a length of 384 mm (15.1 in)

Tube Specification

Material:	PVC
Max surface resistance:	10 to 1000 MΩ/sq
Color:	Transparent
Capacity:	10 pcs/tube
Weight:	typ 160 g
End stops	Pins

Reliability

According to MIL-HDBK-217F the calculated MTBF value at 100% load (from PKV 5211 PI) at the following ambient temperatures will be approx.:

T _{amb}	Hours
0 °C	2.7 million
10 °C	1.5 million
25 °C	650 000
40 °C	276 000
60 °C	88 000
75 °C	37 000

At 80–100% load the case temperature will be approx. 15–20 °C higher than the ambient temperature.

Compatibility with RoHS requirements

The products are compatible with the relevant clauses and requirements of the RoHS directive 2011/65/EU and have a maximum concentration value of 0.1% by weight in homogeneous materials for lead, mercury, hexavalent chromium, PBB and PBDE and of 0.01% by weight in homogeneous materials for cadmium.

Exemptions in the RoHS directive utilized in Flex products are found in the Statement of Compliance document.

Flex fulfills and will continuously fulfill all its obligations under regulation (EC) No 1907/2006 concerning the registration, evaluation, authorization and restriction of chemicals (REACH) as they enter into force and is through product materials declarations preparing for the obligations to communicate information on substances in the products.

Quality Statement

The PKV series DC/DC converters are designed and manufactured in an industrial environment where quality systems and methods like ISO 9000 and SPC are intensively in use to boost the continuous improvements strategy. Infant mortality or early failures in the products are screened out by a burn-in procedure.

Warranty

Warranty period and conditions are defined in Flex General Terms and Conditions of Sale.

Limitation of liability

Flex does not make any other warranties, expressed or implied including any warranty of merchantability or fitness for a particular purpose (including, but not limited to, use in life support applications, where malfunctions of product can cause injury to a person's health or life).

© Flex 2023

The information and specifications in this technical specification is believed to be correct at the time of publication. However, no liability is accepted for inaccuracies, printing errors or for any consequences thereof. Flex reserves the right to change the contents of this technical specification at any time without prior notice.

Product Program

V_I	V_O/I_O max	P_O max	Ordering No.
12/24 V	5 V/500 mA	2.5 W	PKV3211PI
	12 V/250 mA	3.0 W	PKV3313PI
	15 V/200 mA	3.0 W	PKV3315PI
	± 5 V/250 mA	2.5 W	PKV3222PI
	±12 V/125 mA	3.0 W	PKV3321PI
	±15 V/100 mA	3.0 W	PKV3325PI
48/60 V	5 V/500 mA	2.50 W	PKV 5211PI
	15 V/200 mA	3.00 W	PKV 5315PI
	± 5 V/250 mA	2.50 W	PKV 5222PI
	±12 V/125 mA	3.00 W	PKV 5321PI
	±15 V/100 mA	3.00 W	PKV 5325PI

Information given in this data sheet is believed to be accurate and reliable. No responsibility is assumed for the consequences of its use nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Flex. These products are sold only according to Flex general conditions of sale, unless otherwise confirmed in writing.

Specifications subject to change without notice.

The latest and most complete information can be found on our website.

Datasheet

28701- BMR 702 Rev.C
© Flex, May 2023

28701- BMR 702 Rev. C © Flex, May 2023